

F

E

D

C

B

A

F

E

D

C

B

A

50— ① — ② — ③ — ④ — ⑤ — ⑥ — ⑦

SWITCH FUNCTION CODE	SWITCH FUNCTION DESCRIPTION
1	MOMENTARY SOLDER TERMINAL
2	MAINTAINED SOLDER TERMINAL
5	MOMENTARY P.C. TERMINAL
6	MAINTAINED P.C. TERMINAL
A	MOMENTARY WIRELEADS
B	MAINTAINED WIRELEADS

HOUSING TYPE CODE	BEZEL TYPE DECSRIPTION
RBK	ROUND, BLACK

LED COLOR CODE	LED COLOR
N	NONE
G	GREEN
R	RED
B	BLUE
W	WHITE
A	AMBER
RB	RED/BLUE
RG	RED/GREEN

BUTTON COLOR CODE	BUTTON COLOR
RD	RED
GR	GREEN
BL	BLUE
BK	BLACK
YL	YELLOW
OR	ORANGE

MOUNTING TYPE CODE	MOUNTING TYPE
B	BUSHING

LED INLET VOLTAGE CODE (SEE LED SPECIFICATION)		LED INLET VOLTAGE
NON-WIRELEADS	IF BLANK	(SEE LED SPECIFICATION TABLE)
	05	5V*
WIRELEADS	IF BLANK	(SEE LED SPECIFICATION TABLE)
	05	5V*
	12	12V
	24	24V

ANY CODE	DESCRIPTION
IF BLANK	NA
XXX	PER CUSTOMER SPECIAL REQUEST

MECHANICAL CHARACTERISTICS:

SWITCH CIRCUITRY: SPST-NO-DB
SWITCH ACTION: MOMENTARY OR MAINTAINED (PER CHART)
BUTTON TRAVEL: 2.3mm NOMINAL
OPERATING FORCE: 306g [3N] NOMINAL
CONTACT BOUNCE: 1ms NOMINAL
PANEL THICKNESS: 0.5 - 3.0mm
CONTACTS: GOLD PLATED
NUT TORQUE FORCE: MAX 6 kgf/cm [5.2 LB/in]

ENVIRONMENTAL SPECIFICATIONS:

ACTUATOR INGRESS PROTECTION: IP67
OPERATING TEMPERATURE:
MOMENTARY: -40°C to +85°C [-40°F to +185°F]
MAINTAINED: -40°C to +65°C [-40°F to +149°F]

ELECTRICAL SPECIFICATIONS:


CURRENT RATINGS: 10mA@12VDC
MOMENTARY: 1000K CYCLES NOMINAL
MAINTAINED: 50K CYCLES NOMINAL
DIELECTRIC STRENGTH: 1,000VAC
INSULATION RESISTANCE: 1G OHM
CONTACT RESISTANCE:
50m OHMS MAX INITIAL(NON-WIRELEADS)
250m OHMS MAX INITIAL(WIRELEADS)

LED SPECIFICATIONS:



CURRENT LIMITING RESISTOR IS REQUIRED TO LIMIT
LED FORWARD CURRENT TO 20mA.
LED CHARACTERISTICS SEE LED SPECIFICATION TABLE
*INNER RESISTOR ONLY FOR LED :RED(5V) / BLUE(5V) / GREEN(5V) / WHITE(5V)

NOTE:

1.SUPPLY HEX NET AND SEALING WASHER BULK IN PACKED


LED SPECIFICATION					
LED CODE	LED SINGLE COLOR		CIRCUITRY	Vf(VDC) TYP.	If (mA)
				Color 1	
A	AMBER			2.0	20
R	RED			2.0	20
B	BLUE			3.1	20
G	GREEN			3.0	20
W	WHITE			3.3	20
RB	RED	BLUE		2.0 (RED) 3.3 (BLUE)	20
RG	RED	GREEN		2.0 (RED) 3.4 (GREEN)	20
Notes: 1.) Hand Soldering Temperature (4mm above from Body) : 320°C for 3 seconds					


WIRELEADS SPECIFICATION					
WIRELEADS TYPE	WIRELEADS SPECIFICATION	SW TERMINAL		LED	
		/	O	+	-
ILLUMINATION	AWG26 / UL1007	BLUE	BLUE	RED	BLACK
NON-ILLUMINATION		BLUE	BLUE	--	--




SEALING WASHER

SUPPLY HEX NUT

DWG TYPE SALES DRAWING	DRAWN c.c.	TOLERANCES: UNLESS OTHERWISE NOTED X.X ± 0.5 X.XX ± 0.2 ANGULAR ±1°	DWG TITLE 50-MECHANICAL MOMENTARY & MAINTAINED						
STATUS RELEASE	REVIEW H.W.		DWG NO. 50-1,2,5,6,A,B						
This document is the intellectual property of ITW Electronic Business Asia Co., Limited and may contain confidential, proprietary, privileged information protected by law. Neither this document nor any information it contains can be reproduced, transformed to any other format, or distributed, without written permission by ITW Electronic Business Asia Co., Limited. 本文件為安得百電器股份有限公司之智慧財產，非經許可不得擷取、複製、轉變成其他形式使用或散佈	APPROVED v.w.	THIRD ANGLE PROJECTION 							
	DATE 2017.10.24	REF: S48-1, 2, 5, 6, A, B	☒ 管制文件 ☐ 非管制文件	Unit mm	SCALE 2 : 1	REV 4	RoHS Compliant	SHEET 1 OF 3	



DWG TYPE SALES DRAWING	DRAWN C.C.	TOLERANCES: UNLESS OTHERWISE NOTED X.X ± 0.5 X.XX ± 0.2 ANGULAR ±1°	DWG TITLE 50-MECHANICAL MOMENTARY & MAINTAINED						
STATUS RELEASE	REVIEW H.W.								
This document is the intellectual property of ITW Electronic Business Asia Co., Limited and may contain confidential, proprietary, privileged information protected by law. Neither this document nor any information it contains can be reproduced, transformed to any other format, or distributed, without written permission by ITW Electronic Business Asia Co., Limited. 本文作為安天德百電股份有限公司之智慧財產，非經許可不得翻取、複製、轉變成其他形式使用或散佈	APPROVED V.W.	THIRD ANGLE PROJECTION 	DWG NO. 50-1,2,5,6,A,B						
	DATE 2017.10.24	REF: S48-1, 2, 5, 6, A, B							

DWG TYPE SALES DRAWING	DRAWN <i>e.e.</i>	TOLERANCES: UNLESS OTHERWISE NOTED X.X ± 0.5 X.XX ± 0.2 ANGULAR ±1°		DWG TITLE 50-MECHANICAL MOMENTARY & MAINTAINED					
STATUS RELEASE	REVIEW <i>H.W.</i>								
This document is the intellectual property of ITW Electronic Business Asia Co., Limited and may contain confidential, proprietary, privileged information protected by law. Neither this document nor any information it contains can be reproduced, transformed to any other format, or distributed, without written permission by ITW Electronic Business Asia Co., Limited. 本文件為安天德百電股份有限公司之智慧財產，非經許可不得複製、變換、轉變成其他形式使用或散佈		APPROVED <i>v.w.</i>	THIRD ANGLE PROJECTION 	DWG NO. 50-1,2,5,6,A,B					
		DATE 2017.10.24	REF: S48-1, 2, 5, 6, A, B	☒ 管制文件 ☐ 非管制文件	Unit mm	SCALE 2 : 1	REV 4	RoHS Compliant	SHEET 3 OF 3