


PART NUMBER	GT-BCMA230L	REV.	B
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
12.11.06	E.C.N. #11148.		A
12.21.11	E.C.N. #10BRDR.		B




ELECTRO-OPTICAL SPECIFICATIONS

- | | | |
|----|---|---------------------------|
| 1. | D.C. FIRING VOLTS (dv/dt < 500 V/s) | 230 |
| 2. | IMPULSE FIRING VOLTS (dv/dt = 100V/us) | : 350 V |
| 3. | PEAK IMPULSE CURRENT (8/20us WAVE) | : 10 KA |
| 4. | D.C.HOLD OVER VOLTS (10/1000us 500A Pk) | : 150 VDC |
| 5. | A.C. DISCHARGE CURRENT (1 SEC X 60Hz) | : 10 A (1s x 10) |
| 6. | A.C. FOLLOW-ON CURRENT (AMPS Pk) | : 10 A |
| 7. | INSULATION RESISTANCE 50 VDC MIN | : >1 X 10 ³ MΩ |
| 8. | INTER-ELECTRODE CAP 1K Hz MAX. | : 1 pF |

ENVIRONMENTAL TESTING

- | | | |
|-----------------|---|------------------------|
| THERMAL SHOCK | : | MIL-STD-200 METHOD 107 |
| | | TEST COND A |
| HUMIDITY | : | MIL-STD-202 METHOD 103 |
| | | TEST COND A |
| LIFE, HIGH TEMP | : | MIL-STD-202 METHOD 108 |
| | | TEST COND D |
| OPERATING TEMP | : | -40°C TO -60°C |



- ① CERAMIC BODY
- ② METAL ELECTRODES

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= ^{+DECIMAL PRECISION}_{-0.00} MAX.= ^{+0.00}_{-DECIMAL PRECISION} UNCONTROLLED DOCUMENT



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
FAX: +1.847.359.6538
WEB: WWW.LUMEX.COM

ARRESTOR 3 LEADED (230 VDC)	
THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.	
CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.	

DATE:	12.21.11	DRAWN BY:	AB
PAGE:	1 OF 1	CHKD BY:	SS
SCALE:	NTS	APRVD BY:	JD
UNIT:	mm [INCH]		Ⓟ