


PART NUMBER	GT-BCM2000L	REV.	D
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
03.29.99	E.C.N. #10BRDR. & REDRAWN & #10504.		A
08.09.01	E.C.N. #10BRDR. & #10774.		B
12.11.06	E.C.N. #11148.		C
12.21.11	E.C.N. #10BRDR.		D



ELECTRICAL SPECIFICATIONS		
CONDITION	SYMBOL	RATING
D.C. FIRING VOLTAGE:	(dv/dt 100V/S)	2000 ±15% VDC
IMPULSE MAX. FIRING VOLTAGE:	(10/200µS 2500V)	2500 VDC
IMPULSE CURRENT (KA):	(8/20µS)	5KA MAX.
IMPULSE SURGE LIFE(X):	(10/200µS 200A)	50 TIMES MIN.
D.C. HOLDOVER VOLTAGE:	(150mS MAX.)	300V D.C.
A.C. DISCHARGE CURRENT:	(1S X 10 TIMES)	10A
A.C. FOLLOW-ON CURRENT:	(1/2 CYCLE, 60Hz)	30A
INSULATION RESISTANCE(MIN.):	(250 VDC)	1000M Ω
INTER-ELECTRODE CAPACITANCE:	(1.0 KHz)	5.0 PF MAX.

ENVIRONMENTAL SPECIFICATIONS PER MIL-STD 202

TEST	METHOD	CONDITION	RATING
VIBRATION TESTING:	204B	C	C10-55Hz, .06DA
THERMAL SHOCK:	107	B	-65 TO +125°C
HUMIDITY:	103B	B	95% Re. HUMIDITY
TEMP CYCLING:	102A	C	-65 TO +125°C
SOLDERABILITY:	208	B	
OPERATION TEMP.	-	-	-40 TO +100°C

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= ^{DECIMAL PRECISION} _{-0.00} MAX.= ^{DECIMAL PRECISION} _{-DECIMAL PRECISION}

UNCONTROLLED DOCUMENT



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
FAX: +1.847.359.6538
WEB: WWW.LUMEX.COM

HEAVY DUTY CERAMIC SURGE PROTECTOR, 2 LEADED.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL
KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	12.21.11	DRAWN BY:	AB
PAGE:	1 OF 1	CHKD BY:	SS
SCALE:	NTS	APRVD BY:	JD
UNIT:	mm [INCH]		Ⓟ