


PART NUMBER	GT-BG90L	REV.	B
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
12.11.06	E.C.N. #11148.		A
12.27.11	E.C.N. #10BRDR.		B



RESPONSE TIME

SURGE TYPE:	(Rt MAX.)
1Kv/ms:	1 X 10 SEC ⁵
1Kv/us:	1 X 10 SEC ⁸
5Kv/us:	1 X 10 SEC ⁹

APPLICABLE ENVIRONMENTAL SPECIFICATIONS

ALL UNITS MEET THE REQUIREMENTS OF MIL-STD 202 AS OUTLINED BELOW

TEST	METHOD	CONDITION	RATING
VIBRATION	204B	C	10-55Hz .06DA
SHOCK	213A	C	100 g
HUMIDITY	103B	B	95% Re. HUMIDITY
TEMPERATURE CYCLING	102A	C	-65°C TO +125°C
BAROMETRIC PRESSURE	105C	B	50,000 ft.
THERMAL SHOCK	107	B	-65°C TO 125°C
SOLDERABILITY	208	B	—

ELECTRICAL SPECIFICATIONS

D.C. FIRING VOLTAGE (dv/dt<100v/s):	90V ±20%
IMPULSE FIRING VOLTAGE (dv/dt=5kv/us):	MAX 1000V
PEAK IMPULSE CURRENT (8/20us PULSE):	5KA
SURGE LIFE:	100A 500 TIMES (8/20us)
INSULATION RESISTANCE:	MIN 10 M ⁴ (DC 50V)
INTER-ELECTRODE CAPACITANCE:	MAX 2PF (1KHz)

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ^{+0.00}/_{-0.00} DECIMAL PRECISION MAX.= ^{+0.00}/_{-0.00} DECIMAL PRECISION

LUMEX
 Creating LED and LCD Solutions Together™
 290 E. HELEN ROAD
 PALATINE, IL 60067-6976
 PHONE: +1.847.359.2790
 FAX: +1.847.359.6538
 WEB: WWW.LUMEX.COM

AXIAL LEADED, SURGE ARRESTOR, 90 VDC.
 THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.
 CONFIDENTIAL INFORMATION
 THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	12.27.11	DRAWN BY:	AB
PAGE:	1 OF 1	CHKD BY:	DT
SCALE:	NTS	APRVD BY:	SS
UNIT:	mm [INCH]		(Pb)