
PART NUMBER	GT-NB6S1925	REV.	В
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
12.12.06	E.C.N. #11148.		Α
01.03.12	E.C.N. #10BRDR. & REDRAWN.		В





	ELECTRO-OPTICAL CHARACTERISTICS				
PARAMETER	MIN	TYP	MAX	UNITS	
OPERATING VOLTAGE	90		115	٧	
STARTING VOLTAGE AC/DC			85/120	V	
OPERATING CURRENT		0.8		mA	
LIGHT OUTPUT		25		mLM	
LIFE HOURS		10,000		HOURS	

NOTES:

1. EXTERNAL RESISTOR VALUE 51K OHMS.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+0.00}_{-0.00}$ PRECISION MAX.= $^{+0.00}_{-0.000}$ PRECISION $^{-0.000}_{-0.000}$ MAX.= $^{+0.00}_{-0.000}$ PRECISION $^{-0.000}_{-0.000}$ PRECISION $^{-0.000}_{-0.0000}$ PRECISION $^{-0.0000}_{-0.0000}$ PRECISION $^{-0.0000}_$ UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

GAS COLOR INDICATOR TUBE, BLUE.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 01.03.12 DRAWN BY: AΒ PAGE: 1 OF 1 CHKD BY: SS SCALE: NTS APRVD BY: JD (Pb) UNIT: mm [INCH]