
UNCONTROLLED DOCUMENT

PART NUMBER	GT-NE6H1925T	REV.	D
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
04.02.98	E.C.N. #10437. & REDRAWN.		Α
10.21.99	E.C.N. #10561. & #10BRDR.		В
12.13.06	E.C.N. #11148.		С
03.29.12	E.C.N. #10BRDR.		D
	DATE 04.02.98 10.21.99 12.13.06	DATE E.C.N. NUMBER AND REVISION COMMENTS 04.02.98 E.C.N. #10437. & REDRAWN. 10.21.99 E.C.N. #10561. & #10BRDR. 12.13.06 E.C.N. #11148.	DATE E.C.N. NUMBER AND REVISION COMMENTS 04.02.98 E.C.N. #10437. & REDRAWN. 10.21.99 E.C.N. #10561. & #10BRDR. 12.13.06 E.C.N. #11148.





	ELECTRO-OPTICAL CHARACTERISTICS							
A	PARAMETER	MIN	TYP	MAX	UNITS			
	OPERATING VOLTAGE	90		115	٧			
	STARTING VOLTAGE(AC)			85	V			
	(DC)			125	٧			
	OPERATING CURRENT:							
	W/ 33K OHM RES.	. 1.3±	20% mA @	110V				
	W/ 82K OHM RES.	. 1.9±	20% mA @	220V				
	LIGHT OUTPUT		111					
	LIFE HOURS		20,000		HOURS			
	EMITTED COLOR:	ORANGE						

B A NOTES:

- 1. PARTS TO BE IN A SEALED BAG WITH DESICANT.
- 2. LEAD DIAMETER: 0.40 [0.016].
- 3. LEAD FINISH: (UT OR BLANK)—T—SILVER PLATED LEADS.
 4. CORONA MUST COVER A MINIMUM OF 25% OF THE ELECTRODE WITH NO FLICKERING.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+0.00}_{-0.00}$ PRECISION MAX.= $^{+0.00}_{-0.000}$ MAX.= $^{+0.00}_{-0.000}$ PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.002), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.003). MIN= $^{+0.00}_{-0.00}$ PRECISION MAX.= $^{+0.00}_{-0.000}$ PRECISION MAX.= $^{+0.000}_{-0.000}$ PRECISION MAX UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM MEMBER OF ITW PHOTONICS GROUP 6mm x 19mm NEON LAMP, ORANGE HIGH BRIGHTNESS.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 03.29.12 DRAWN BY: PAGE: 1 OF 1 CHKD BY: SS SCALE: NTS APRVD BY: SS UNIT: mm [INCH]