



| PART NUMBER | GT-SMD18123502-TR                   | REV. | B    |
|-------------|-------------------------------------|------|------|
| DATE        | E.C.N. NUMBER AND REVISION COMMENTS |      | REV. |
| 12.19.06    | E.C.N. #11148.                      |      | A    |
| 02.24.09    | E.C.N. #11622.                      |      | B    |




| ELECTRICAL SPECIFICATIONS    |                         |                  |
|------------------------------|-------------------------|------------------|
| PARAMETER                    | VALUE                   | TEST CONDITION   |
| D.C. FIRING VOLTAGE:         | 350V±20% D.C.           | (dv/dt 100V/S)   |
| IMPULSE FIRING VOLTAGE:      | 700V D.C. MAX.          | 1KV/μS           |
| IMPULSE CURRENT:             | 2KA MAX.                | (8/20μS)         |
| A.C. DISCHARGE CURRENT:      | 2a                      | (50Hz, 9 CYCLES) |
| INSULATION RESISTANCE:       | 10 <sup>4</sup> MΩ MIN. | 50 VDC           |
| INTER-ELECTRODE CAPACITANCE: | 1.0 PF MAX.             | 1.0kHz           |

| ENVIRONMENTAL SPECIFICATIONS PER MIL-STD 202 |         |           |                  |
|----------------------------------------------|---------|-----------|------------------|
| TEST                                         | METHODE | CONDITION | RATING           |
| VIBRATION TESTING:                           | 204B    | C         | 10-55HZ, 06DA    |
| SHOCK:                                       | 213A    | C         | 100G             |
| HUMIDITY:                                    | 103B    | B         | 95%RE.HUMIDITY   |
| TEMPERATURE CYCLING:                         | 102A    | C         | - 65 TO + 125 °C |
| BAROMETRIC PRESSURE:                         | 105C    | B         | 50,000FT.        |
| THERMAL SHOCK:                               | 107     | B         | - 65 TO + 125 °C |
| SOLDERABILITY:                               | 208     | B         |                  |




RECOMMENDED SOLDER PAD LAYOUT



LEAD FREE REFLOW PROFILE

10 SEC. MAX.



TOTAL TIME ABOVE 220°C IS 60 SECONDS MAX.

## B NOTES:

- 2000 PIECES PER REEL.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION -0.00 MAX.= +0.00 -DECIMAL PRECISION



290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
FAX: +1.847.359.6538  
WEB: WWW.LUMEX.COM

3.2 x 4.5mm SURFACE MOUNT SURGE, ARRESTOR, 350V.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

|        |           |           |      |
|--------|-----------|-----------|------|
| DATE:  | 12.19.06  | DRAWN BY: | JN   |
| PAGE:  | 1 OF 1    | CHKD BY:  | KF   |
| SCALE: | N/A       | APRVD BY: | SS   |
| UNIT:  | mm [INCH] |           | (Pb) |