


PART NUMBER	GT-SMD181240023-TR	REV.	C
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
12.19.06	E.C.N. #11148.		A
02.24.09	E.C.N. #11622.		B
10.22.12	E.C.N. #11837.		C




ELECTRICAL SPECIFICATIONS



PARAMETER	VALUE	TEST CONDITION
D.C. FIRING VOLTAGE	400V±30% D.C.	(dv/dt 100V/S)
IMPULSE CURRENT	2KA MAX.	(8/20μS)
A.C. DISCHARGE CURRENT	2A MAX.	(50Hz, 9 CYCLES)
INSULATION RESISTANCE	10 ⁴ MΩ MIN.	50V DC
INTER-ELECTRODE CAPACITANCE	1.0 PF MAX.	1.0kHz

ENVIRONMENTAL SPECIFICATIONS PER MIL-STD 202

TEST	METHODE	CONDITION	RATING
VIBRATION TESTING	204B	C	10-55Hz, .06DA
SHOCK	213A	C	100G
HUMIDITY	103B	B	95%RE HUMIDITY
TEMPERATURE CYCLING	102A	C	-65 TO +125°C
BAROMETRIC PRESSURE	105C	B	50,000 FT
THERMAL SHOCK	107	B	-65 TO +125°C
SOLDERABILITY	208	B	



RECOMMENDED SOLDER PAD LAYOUT



[B] NOTES:

- 2000 PIECES PER REEL.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION MAX.= +DECIMAL PRECISION -0.00

UNCONTROLLED DOCUMENT

3.2 x 4.5mm SURFACE MOUNT SURGE, ARRESTOR, 400V.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	10.22.12	DRAWN BY:	AB
PAGE:	1 OF 1	CHKD BY:	SS
SCALE:	NTS	APRVD BY:	SS
UNIT:	mm [INCH]		(Pb)