


UNCONTROLLED DOCUMENT

PART NUMBER
IFL-LX73-22633

REV.
A

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #11148.	04.11.07



ELECTRO-OPTICAL SPECIFICATIONS

VOLTAGE:	14.0 VAC OR VDC
AMPERAGE:	80 mA +/-10%
INTENSITY:	.30 MSCP @ 14.0 X
OPERATING LIFE:	15,000 HRS @ 14.0 VAC

MECHANICAL SPECIFICATIONS

BULB TYPE/STYLE:	T-1 3/4 AMERICAN T 5.8 METRIC
BASE TYPE:	ALL GLASS WEDGE
ANSI SPECIFICATION:	73

ENVIRONMENTAL SPECIFICATIONS

VIBRATION TESTING:	MIL-E-5400N, GRAPH IV
SHOCK:	MIL-STD-883 METHOD 2002 TEST COND A
OPERATING TEMPERATURE:	-50 TO +100 DEG.C
STORAGE TEMPERATURE:	-50 TO +125 DEG.C

NOTES:

1. IFL-LX73
2. GREEN SILICON BOOT: x= .37, y= .62



UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= -0.00 +0.00 DECIMAL PRECISION MAX.= -0.00 +0.00 DECIMAL PRECISION

REV.
A

PART NUMBER
IFL-LX73-22633

T-1 3/4 WEDGE BASE, INCANDESCENT LAMP
WITH GREEN BOOT ATTACHED.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: JC	CHECKED BY:	APPROVED BY:	DATE: 4.17.96 PAGE: 1 OF 1 SCALE: N/A
-----------------	-------------	--------------	---