UNCONTROLLED DOCUMENT

	5,8 (.23) DIA. MAX
15.2 (.60)	

5.1 (.20) MAX

- 5.1 (.20) MAX

PART NUMBER IFL-LX73

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	REDRAWN./	6.1.93
В	E.C.N. #11148.	04.12.07

ELECTRO-OPTICAL SPECIFICATIONS

14.0 VAC OR VDC VOLTAGE: 80 mA +/-10%AMPERAGE: .3D MSCP @ 14.0 X INTENSITY: 15.000 HRS @ 14.0 VAC OPERATING LIFE:

MECHANICAL SPECIFICATIONS

BULB TYPE/STYLE: T-1 3/4 AMERICAN T 5.8 METRIC

BASE TYPE: ALL GLASS WEDGE

P/N MARKING ON LAMP: 73 ANSI SPECIFICATION: 73

ENVIRONMENTAL SPECIFICATIONS

VIBRATION TESTING: MIL-E-5400N, GRAPH IV

SHOCK: MIL-STD-883 METHOD 2002 TEST COND A

OPERATING TEMPERATURE: -50 TO +100 DEG.C STORAGE TEMPERATURE: -50 TO +125 DEG.C



REV.

UNCONTROLLED DOC **UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.002), LEAD LENGTH=±0.75 (±0.002), MIN= +DECINAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.127 (±0.005).

REV. PART NUMBER IFL-LX73

T-1 3/4 WEDGE BASE, INCANDESCENT LAMP.

3.0 (.12) MAX ^{_1}

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



JC

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359,2790 US WEB: www.lumex.com

TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY:

DATE: 10,20.86 PAGE: 1 OF 1 SCALE: N/A