

UNCONTROLLED DOCUMENT

PART NUMBER
IFL-LXAF82914250

REV.


A

REV. E.C.N. NUMBER AND REVISION COMMENTS

DATE

A E.C.N. #11148.

4.13.07



ELECTRO-OPTICAL SPECIFICATIONS

OPERATING VOLTAGE	:	14.0V
RATED CURRENT	:	250+/-10% mA
LIGHT INTENSITY	:	15 LUMENS +/-25%
AVERAGE LIFE	:	600 HRS (CATASTROPHIC)

PROCESS AND MATERIAL SPECIFICATIONS

BASE CAPS	:	S7 (2)
GLASS TYPE	:	SOFT K12
GLASS FILL	:	VACCUUM
FILAMENT	:	TUNGSTEN RHEENIUM ALLOY
AGING CYCLE	:	16 HRS MIN.



UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION -0.00 MAX.= +0.00 -DECIMAL PRECISION

REV.

A

PART NUMBER

IFL-LXAF82914250

AXIAL FESTOON INCANDESCENT LAMP,
T8 x 29 S7 CAPS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JC

CHECKED BY:

APPROVED BY:

DATE: 11.11.93

PAGE: 1 OF 1

SCALE: N/A