


UNCONTROLLED DOCUMENT

PART NUMBER
IFL-LXW419050GB

REV.
A

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #11148.	4.16.07



ELECTRICAL SPECIFICATIONS W/O BOOT ATTACHED

OPERATING VOLTAGE VAC. OR VDC.	1B-20V
DESIGN VOLTAGE VAC. OR VDC.	19V
CURRENT DRAW @ DESIGN VOLTS	50 mA
M.S.C.P. @ DESIGN VOLTS	0.25±25% M.S.C.P.
AVERAGE LIFE @ DESIGN VOLTS (AC)	5,000 HOURS

MECHANICAL SPECIFICATIONS

BULB SIZE & SHAPE	T4mm TUBULAR
BULB GLASS TYPE	K12 SOFT GLASS
BASE OR LEAD FINISH	TINNED
FILAMENT SHAPE	C-2F
MANUFACTURING P55	T3nW 3044

ENVIRONMENTAL SPECIFICATIONS

VIBRATION TESTING	MIL-E-5400N, GRAPH IV
SHOCK TEST	MIL-STD-883 METHOD 2002 TEST CONDITION A
OPERATION TEMP.	- 50 TO +100 °C
STORAGE TEMP.	- 50 TO +125 °C
SOLDERABILITY OF LEADS	MIL-STD 202F, METHOD 208D

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION

REV.
A

PART NUMBER
IFL-LXW419050GB

T-4mm (T-1 1/4) SUB MINIATURE LAMP,
19 VOLTS, 50 mA, GLASS BI-PIN.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 6.8.98
jc			PAGE: 1 OF 1
			SCALE: N/A