


UNCONTROLLED DOCUMENT

PART NUMBER
IFS-LX4F-3052YD-9REV.
B

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	RDW & UPD SAFE OPER. SPEC. ADDED BOM	10.13.94
B	E.C.N. #11148.	02.02.07



Ⓐ B.Q.M.

1. SSL-LX3054YD OR SSL-LX3052YD AS ALTERNATE.
2. IFS-LX4FRA RIGHT ANGLE HOLDER.
3. CUT LED LEADS TO 5mm. INSERT LED INTO HOLDER WITH POLARITY AS SHOWN.

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C				I _f =20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		585 (YELLOW)		nm	
FORWARD VOLTAGE		2.1	2.8	V _f	
REVERSE VOLTAGE	5.0			V _r	I _r =100μA
AXIAL INTENSITY		4.0		mcd	I _f =20mA
VIEWING ANGLE		80		2x theta	
EMITTED COLOR :	YELLOW				
EPOXY LENS FINISH:	YELLOW DIFFUSED				

LIMITS OF SAFE OPERATION AT 25 DEG. C

PARAMETER	MAX	UNITS
Ⓐ PEAK FORWARD CURRENT *	150	mA
Ⓐ STEADY CURRENT	30	mA
Ⓐ POWER DISSIPATION	105	mW
DERATE FROM 25 °C	-1.6	mW/ °C
Ⓐ OPERATING, STORAGE TEMP.	-40 TO +85	°C
Ⓐ LEAD SOLDERING TEMP.	+260	°C
Ⓐ 2.0mm FROM BODY		3 SEC. MAX

* t<10μS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.038), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX= +0.00 -DECIMAL PRECISION

REV.
BPART NUMBER
IFS-LX4F-3052YD-9

T-3 (T-1) LED, RIGHT ANGLE, YELLOW DIFFUSED.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 11.12.91
jc			PAGE: 1 OF 1
			SCALE: N/A

UNCONTROLLED DOCUMENT