




UNCONTROLLED DOCUMENT

LCD-H401M50KF-1


P1

PRELIMINARY IN P/N DIR



NOTES:

1. CIRCLE SEGMENTS, S1-S4 ARE EACH SINGLE SEGMENTS
2. FLASH ICON, AS S5 AND S6, ARE TWO SEGMENTS EACH.
3. m, s, V, A, h ARE ALL SEPERATE SEGMENTS.



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION -0.00 MAX.= +0.00 -DECIMAL PRECISION

UNCONTROLLED DOCUMENT

REV.

PART NUMBER

P1

LCD-H401M50KF-1

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

0.4" CUSTOM SEGMENT LCD DISPLAY,

3.0V TN POSITIVE, 12:00 VIEW, EXTENDED OPERATING TEMP.

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 06.11.08

JN

PAGE: 2 OF 2

SCALE: N/A