


UNCONTROLLED DOCUMENT


PART NUMBER
LCD-S301M31TR-S

REV.

A

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	ECN # 11374.	12.06.06

CHARACTERISTICS	
FLUID TYPE:	TN
BACKGROUND COLOR:	GRAY
VIEWING DIRECTION:	6:00
DISPLAY MODE:	REFLECTIVE
OPERATING VOLTAGE:	5V A.C.
OPERATING TEMP.	0°C TO 50°C
STORAGE TEMP.	-20°C TO 70°C
DRIVING METHODE:	STATIC
CONNECTION TYPE:	FPC



NOTES:

1. COOLER AND WARMER ARE ONE SEGMENT.
2. TEXT HEIGHT = 0.75mm

PIN NO.	1	2	3	4	5	6	7	8	9	10	11
SEGMENT	COM	S5	S4	S3	S2	S1	DUCT	PRESSURE	FLOW	G3	B3
PIN NO.	12	13	14	15	16	17	18	19	20	21	22
SEGMENT	A3	F3	G3	E3	D3	C2	B2	A2	F2	G2	E2
PIN NO.	23	24	25	26	27	28	29	30	31	32	33
SEGMENT	D2	C1	B1	A1	F1	G1	E1	D1	S7	S6	COM

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV.

A

PART NUMBER

LCD-S301M31TR-S

3 DIGIT CUSTOM LCD PANEL, TN, REFLECTIVE,
WITH FPC.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 12.06.06
JC			PAGE: 1 OF 1
			SCALE: N/A



UNCONTROLLED DOCUMENT