



PART NUMBER	LCD-S801D10TR	REV.	B
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
02.09.07	E.C.N. #11148.		A
12.05.11	E.C.N. #10BRDR. & REDRAWN.		B



CHARACTERISTICS	
FLUID TYPE:	TN
BACKGROUND COLOR:	GRAY
VIEWING DIRECTION:	6:00
DISPLAY MODE:	REFLECTIVE
OPERATING VOLTAGE:	3.0~5.0V AC.
OPERATING TEMP.	0°C TO 50°C
STORAGE TEMP.	-20°C TO 70°C
DRIVING METHODE:	STATIC
CONNECTION TYPE:	64 PINS

CHARACTER DETAIL



PIN NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
SEGMENT	COM	1E	1D	1C	DP1	2E	2D	2C	DP2	3E	3D	3C	DP3	4E	4D	4C
PIN NO.	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
SEGMENT	DP4	5E	5D	5C	DP5	6E	6D	6C	DP6	7E	7D	7C	DP7	8E	8D	8C
PIN NO.	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48
SEGMENT	8B	8A	8F	8G	7B	7A	7F	7G	6B	6A	6F	6G	5B	5A	5F	5G
PIN NO.	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64
SEGMENT	4B	4A	4F	4G	3B	3A	3F	3G	2B	2A	2F	2G	1B	1A	1F	1G

REPLACES PART #: LCD-S100C801TR

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION

 LUMEX Creating LED and LCD Solutions Together™	290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM	1.00" CHARACTER HEIGHT, EIGHT DIGIT LCD GLASS, TN, REFLECTIVE, 64 PINS.		DATE: 12.05.11	DRAWN BY: AB
		THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.		PAGE: 1 OF 1	CHKD BY: SS
		CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.		SCALE: NTS	APRVD BY: KF
				UNIT: mm [INCH]	Ⓟ