



UNCONTROLLED DOCUMENT



NOTES:

1. THIS SIDE HEAT SEALED TO PCB.
2. CONDUCTOR PAD COUNT NEEDS TO BE EXACTLY 19.
3. NO ANTI-GLARE ON FRONT POLARIZER.
4. POLARIZER TYPE: SHC.

5. HEAT SEAL: 1905100-10.9KN



UNCONTROLLED DOCUMENT


*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+0.001 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV. E	PART NUMBER LCD-UH201A30TB-1S	CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.	 290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw	
TWO 0.28" ALPHANUMERIC DIGITS, CUSTOM LCD PANEL, GRAPHITE HEAT SEAL CONNECTOR, BLACK MASK TN, TRANSMISSIVE, NEGATIVE IMAGE.		DRAWN BY: JC	CHECKED BY: APPROVED BY:	DATE: 10.9.01 PAGE: 1 OF 2 SCALE: N/A

UNCONTROLLED DOCUMENT

PART NUMBER
LCD-UH201A30TB-1SREV.
EREV. E C.N. NUMBER AND REVISION COMMENTS
SEE PAGE #1

DATE



CHARACTERISTICS	
FLUID TYPE	TN
BACKGROUND COLOR	BLACK MASK
VIEWING DIRECTION	12:00
DISPLAY MODE	TRANSMISSIVE
OPERATING VOLTAGE	5.0V A.C.
OPERATING TEMP.	-30°C TO 85°C
STORAGE TEMP.	-40°C TO 85°C
DRIVING METHOD	1/2 DUTY, 1/2 BIAS
CONNECTION TYPE	19 PAD HEAT SEAL CABLE

PIN NO.	1	2	3	4	5	6	7	8	9	10
COM 1	2D	2E	2F	2G	DP	1D	1E	1F	1G	1H
COM 2	2M	2N	2O	2P	/	1M	1N	1O	1P	1I
PIN NO.	11	12	13	14	15	16	17	18	19	
COM 1	1A	1B	1C	2H	2A	2B	2C	COM1	/	
COM 2	1J	1K	1L	2I	2J	2K	2L	/	COM2	

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+DECIMAL PRECISION MAX.=+0.00 -DECIMAL PRECISION

REV.
EPART NUMBER
LCD-UH201A30TB-1S

TWO 0.28" ALPHANUMERIC DIGITS, CUSTOM LCD PANEL,
GRAPHITE HEAT SEAL CONNECTOR,
BLACK MASK TN, TRANSMISSIVE, NEGATIVE IMAGE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:
JC

CHECKED BY:

APPROVED BY:

DATE: 10.9.01
PAGE: 2 OF 2
SCALE: N/A

UNCONTROLLED DOCUMENT