


PART NUMBER		REV.
LCD-UH601D10TM		A
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #11148.	4.17.07



PIN NO.	1	2	3	4	5	6	7	8	9	10
SEGMENT	COM	E6	D6	C6	DP5	E5	D5	C5	DP4	E4
PIN NO.	11	12	13	14	15	16	17	18	19	20
SEGMENT	D4	N/C	N/C	N/C	N/C	C4	N/C	DP3	E3	D3
PIN NO.	21	22	23	24	25	26	27	28	29	30
SEGMENT	N/C	N/C	N/C	C3	N/C	DP2	E2	D2	N/C	N/C
PIN NO.	31	32	33	34	35	36	37	38	39	40
SEGMENT	C2	DP1	E1	D1	C1	B1	A1	F1	G1	B2
PIN NO.	41	42	43	44	45	46	47	48	49	50
SEGMENT	A2	F2	G2	COL1	N/C	B3	N/C	N/C	N/C	A3
PIN NO.	51	52	53	54	55	56	57	58	59	60
SEGMENT	F3	G3	N/C	N/C	B4	N/C	N/C	A4	F4	G4
PIN NO.	61	62	63	64	65	66	67	68	69	70
SEGMENT	COL2	B5	A5	F5	G5	B6	A6	F6	G6	COM

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.= $\frac{+0.001}{-0.000}$ DECIMAL PRECISION, MAX.= $\frac{+0.001}{-0.000}$ DECIMAL PRECISION

PART NUMBER
LCD-UH601D10TM

1" 6 DIGIT 7 SEGMENT LCD DISPLAY, TN, TRANSMISSIVE,
-40°C TO 85°C OPERATING TEMPERATURE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DENNEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



UNCONTROLLED DOCUMENT



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 11.15.01
JC			PAGE: 1 OF 1
			SCALE: N/A