





PART NUMBER		REV.
LCM-H12864CGWF/C		P1
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10866.	5.20.02
B	E.C.N. #10975.	4.8.03
C	E.C.N. #11020.	7.30.03
D	E.C.N. #11049.	11.4.03



NOTES:

1. POLARIZER
2. IC: S1D15605D01B OR S1D15605D00B.
3. OPERATING TEMPERATURE: -20°C TO +70°C.
4. STORAGE TEMPERATURE: -30°C TO +80°C.
5. DUTY CYCLE: 1/64, 1/7 BIAS.
6. PART IDENTIFICATION: PART NUMBER: 41-136498-001 AND DATE CODE SHALL BE PLACED IN OR ON THE EDGE NEAR THE NON VIEWABLE AREA INDICATED, OR PLACED ON THE TAIL OR PLACED ON A LABEL ON THE TAIL.
7. LXP-H12864-EMI.
8. V_{LED} = 9.7V TO 10.3V
9. LCD MEETS CONTRAST ADJUSTMENT FROM 1 TO 9.
10. V_{LED} = DOES NOT FLUCTUATE FROM MENU TO MENUS.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION -0.00 MAX.= +0.00 -DECIMAL PRECISION

REV.	PART NUMBER
P1	LCM-H12864CGWF/C
128 x 64 CHIP ON GLASS LCD MODULE, FSTN, TRANSFLECTIVE, -20°C TO +70°C OPERATING TEMP, 6:00 VIEW ANGLE, 1/64 DUTY, 1/7 BIAS.	

CONFIDENTIAL INFORMATION
 THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
 OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

290 E. HELEN ROAD
 PALATINE, IL 60067-6976
 PHONE: +1.847.359.2790
 US WEB: www.lumex.com
 TW WEB: www.lumex.com.tw

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE:
CT			3.15.02
			PAGE: 1 OF 5
			SCALE: N/A