



LCM-S02004DQ38897

PRELIMINARY IN P/N DIR




CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

NOTES:

- 0.6mm THICK SILK SCREEN ON FRONT PANEL UNLESS OTHERWISE SPECIFIED.
- 16 PIN SINGLE ROW HEADER, SAMTEC PART#: MTSW-116-07-S-S-215 OR EQUIVALENT.

CHARACTER DETAIL



TOP & BOTTOM=
1.100 [0.043]
MIDDLE GAP=
1.575 [0.062]

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.038), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION -0.00 MAX.= +0.00 -DECIMAL PRECISION

REV.

PART NUMBER

LCM-S02004DQ38897

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 6.25.07

PAGE: 1 OF 1

SCALE: N/A

4.99mm CHARACTER HEIGHT, 20 x 4 CHARACTER LCD
MODULE, TOP VIEW, STN, YELLOW-GREEN BACKGROUND,
TRANSFLECTIVE W/LED BACKLIGHT, 1/33 DUTY, 16 PINS.

JIN