



LCM-S160160GWF-NBK


PRELIMINARY IN P/N DIR.



PIXEL DETAIL



BLOCK DIAGRAM 160 x 160, 1/160 DUTY



CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+0.00 (0.00), MAX.=+0.00 (0.00).

REV.

PART NUMBER

LCM-S160160GWF-NBK

160 x 160 DOT MATRIX GRAPHIC MODULE,
1/160 DUTY, FSTN WITH NEGATIVE CHARGE PUMP.
TRANSFLECTIVE, NO BACKLIGHT.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 9.10.01

PAGE: 1 OF 2

SCALE: N/A


SA/CT

PIN CONFIGURATION

PIN NO.	SYMBOL	LEVEL	FUNCTION
1	V _{ss}	0V	GND
2	V _{DD}	5V	SUPPLY VOLTAGE FOR LOGIC
3	V _o	-	CONTRAST VOLTAGE FOR LCD DRIVE(VARIABLE)
4	R _D	L	READ SIGNAL
5	W _R	L	WRITE SIGNAL
6	C _S	L	CHIP SELECT
7	A _D	H/L	DATA TYPE SELECT
8~15	D _{B0} ~D _{B7}	H/L	DATA BUS
16	R _{ES}	L	RESET SIGNAL (NOTE 1)
17	V _{EE}	-	POWER SUPPLY VOLTAGE FOR LCD
18	A	4.2V	NO CONNECTION
19	K	-	NO CONNECTION
20	(N/C)	-	NO CONNECTION

NOTES:

1. R_{ES} IS A SCHMITT TRIGGER INPUT. THE PULSEWIDTH ON R_{ES} MUST BE AT LEAST 200 μ s. PULSES OF MORE THAN A FEW SECONDS WILL CAUSE DC VOLTAGES TO BE APPLIED TO THE LCD PANEL.

V_{DD}-V_o: LCD DRIVING VOLTAGEV_R: 10K Ω - 20K Ω 

ELECTRICAL CHARACTERISTICS

V_{DD}=4.75V to 5.25V, T_A=25°C

ITEM		SYMBOL	CONDITION	STANDARD VALUE			UNIT
				MIN.	TYP.	MAX.	
SUPPLY VOLTAGE FOR LOGIC		V _{DD} -V _{ss}	-	4.75	5.0	5.25	V
SUPPLY VOLTAGE FOR LCD DRIVE		V _{DD} -V _{EE}	-	-	18.2	-	V
SUPPLY CURRENT FOR LOGIC		I _{DD}	-	-	-	20	mA
INPUT VOLTAGE	HIGH	V _{IH}	-	0.2	-	V _{DD}	V
	LOW	V _{IL}	-	0	-	0.8	V
OUTPUT VOLTAGE	HIGH	V _{OH}	I _{OH} =-3.0mA	2.4	-	-	V
	LOW	V _{OL}	I _{OL} =3.0mA	-	-	0.4	V
*LED BACKLIGHT	VOLTAGE	V _f	I _f =560mA	-	4.2	4.5	V
	CURRENT	I _f	-	-	560	-	mA
	POWER CONSUMPTION	P _D	-	-	2.8	-	W
	LUMINOUS	L	I _f =560mA	60	-	-	cd/m ²
	COLOR	-	-	-	570	-	nm

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	TEST CONDITION	STANDARD VALUE		UNIT
			MIN	MAX	
SUPPLY VOLTAGE FOR LOGIC	V _{DD} -V _{ss}	T _a =25°C	0	7.0	V
SUPPLY VOLTAGE FOR LCD DRIVE	V _{DD} -V _{EE}	-	17.2@40°C	19.2@0°C	V
INPUT VOLTAGE	V _I	T _a =25°C	V _{ss}	V _{DD}	V
OPERATING TEMPERATURE	T _{opr}	LCM-S	0	50	°C
		LCM-H	-20	70	°C
STORAGE TEMPERATURE	T _{stg}	LCM-S	-20	70	°C
		LCM-H	-30	85	°C

*ONLY APPLIES TO MODULES WITH BACKLIGHT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX=-DECIMAL PRECISION

REV.

PART NUMBER

LCM-S160160GWF-NBK

160 x 160 DOT MATRIX GRAPHIC MODULE,
1/160 DUTY, FSTN WITH NEGATIVE CHARGE PUMP.
TRANSFLECTIVE, NO BACKLIGHT.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

SA/CT

CHECKED BY:

APPROVED BY:

DATE: 9.10.01

PAGE: 2 OF 2

SCALE: N/A