


UNCONTROLLED DOCUMENT


PIN CONFIGURATION				
PIN NO.	SYMBOL	LEVEL	FUNCTION	
1	V _{SS}	-	POWER SUPPLY	GND (0V)
2	V ₅	-		FOR LCD DRIVE
3	V _{DD}	-		5V
4	RS	H/L	REGISTER SELECT SIGNAL H: DATA INPUT L: INSTRUCTION INPUT	
5	R/W	H/L	H: DATA READ (MODULE-->MPU) L: DATA WRITE (MODULE<--MPU)	
6	E	H,H->L	ENABLE	
7~14	DB0~DB7	H/L	DATA BUS--SOFTWARE SELECTABLE 4 OR 8 BIT MODE.	

PIN CONFIGURATION	
PAD NO.	CONFIGURATION
1	COM1[C1(R1-R80)]
8	COM8[C8(R1-R80)]
9	SEG1[R1(C1-C16)]
88	SEG80[R80(C1-C16)]
89	COM16[C16(R1-R80)]
96	COM9[C9(C1-C16)]



ELECTRICAL CHARACTERISTICS		V _{DD} =4.7V to 5.3V, T _A =25°C				
ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
SUPPLY VOLTAGE FOR LOGIC	V _{DD} -V _{SS}	-	MIN.	TYP.	MAX.	
SUPPLY CURRENT FOR LOGIC	I _{DD}	V _{DD} =5V	-	2.0	3.0	mA
INPUT VOLTAGE	HIGH	V _{IH}	2.2	-	V _{DD}	V
	LOW	V _{IL}	-0.3	-	0.8	V
OUTPUT VOLTAGE	HIGH	V _{OH}	I _{OH} =-0.25mA	2.4	-	V
	LOW	V _{OL}	I _{OL} =1.2mA	-	-	V
DRIVER VOLTAGE	COM	V _{COM}	I _D =5μA	-	-	V
	SEG	V _{SEG}	I _D =5μA	-	-	V
INPUT LEAKAGE CURRENT	I _{IL}	V _{IN} =0 TO V _{DD}	-1	-	1	μA
PULL-UP MOS CURRENT	-I _P	V _{DD} =5V	50	125	250	μA
SUPPLY CURRENT POWER	I _{OP}	Rf OSCILL. FROM FROM EXT. CLOCK VDD=5V fosc=FCP=540KHz	-	1	1.5	mA

V_{DD}-V₅: LCD DRIVING VOLTAGE
VR: 10KΩ-20KΩ



ABSOLUTE MAXIMUM RATINGS					
ITEM	SYMBOL	TEST CONDITION	STANDARD VALUE		UNIT
SUPPLY VOLTAGE FOR LOGIC	V _{DD} -V _{SS}	T _a =25°C	-0.3	7.0	V
SUPPLY VOLTAGE FOR LCD DRIVE	V _{DD} -V ₅	-	0	V _{DD} +0.3	V
INPUT VOLTAGE	V _I	T _a =25°C	V _{SS}	V _{DD}	V
OPERATING TEMPERATURE	T _{opr}	LCM-S	0	50	°C
		LCM-H	-20	70	°C
STORAGE TEMPERATURE	T _{stg}	LCM-S	-20	70	°C
		LCM-H	-30	85	°C

*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010")

REV.

PART NUMBER

LCM-X01602CGXX/A

4.35mm CHARACTER HEIGHT, 5 x 8 DOT MATRIX,
16 x 2 C.O.G LCD MODULE, 1/16 DUTY, 1/5 BIAS, 6:00 VIEW.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 6.22.06

PAGE: 2 OF 2

SCALE: N/A

JD