


PART NUMBER	LDM-TPR151509D	REV	X1

REV	E.C.N. NUMBER AND REVISION COMMENTS	DATE
X1	--	10.23.26


PRELIMINARY








CIRCUIT DIAGRAM



APLLICATION CIRCUIT



ELECTRO-OPTICAL CHARACTERISTIC TA=25℃ PER LED

PARAMETER		MIN	TYP	MAX	UNITS	TEST COND
CHROMATICITY COORDINATE	X	-	0.28	-	-	If=5mA
	Y	-	0.27	-	-	
FORWARD VOLTAGE		-	2.8	3.6	Vf	If=5mA
REVERSE CURRENT		-	-	10	uA	VR=5V
LUMINOUS INTENSITY		-	40000	-	ucd	If=5mA
EMITTED COLOR		WHITE				
FONT COLOR		BLACK				
SEGMENT COLOR		MILKY WHITE DIFFUSED				

ABSOLUTE MAXIMUM RATINGS TA=25℃ PER LED

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	60	mA
FORWARD CURRENT	20	mA
POWER DISSIPATION	50	mW
REVERSE VOLTAGE	5	V
STORAGE TEMPERATURE	-40 TO +85	℃
OPERATING TEMPERATURE	-40 TO +85	℃
LEAD SOLDER TEMPERATURE	4 SEC MAX @260	℃

* 1/10 DUTY,1KHz

STATIC DEVICE FOLLOW PROPER
E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+\text{DECIMAL PRECISION}}_{-0.00}$ MAX.= $^{+0.00}_{-\text{DECIMAL PRECISION}}$

ITW LUMEX
Creating LED · LCD & Switch Solutions

2325. KENYON ROAD.
BARTLETT, IL 60103
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

15.0mm(L)*15.0mm(W), TOUCH PAD WITH ICON LED DISPLAY, WHITE COLOR, BLACK FACE, WHITE DIFFUSED SEGMENT.

****THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE.****

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE : 2026.10.29	DRAWN BY : E.C.
PAGE : 1 OF 1	CHKD BY : T.S.
SCALE : NTF	APRVD BY : --
UNIT : mm [INCH]	Pb