


LDS-A3923RISY-BIN2


REV.











ELECTRO-OPTICAL	CHARACTERISTICS	Ta=25°C	lf=10mA		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		590		nm	
FORWARD VOLTAGE		2.0	2.5	Vf	
REVERSE VOLTAGE	5.0			Vr	Ir=100μA
AXIAL INTENSITY		SEE BELOW		μcd	If=10mA
EMITTED COLOR:	YELLOW				
FACE COLOR:	GRAY				
EPOXY LENS FINISH	H: MILKY WHITE	DIFFUSED			


BIN CODE	R	S
INTENSITY RANGE (μcd @ 10mA)	13500~17549	17550~26325

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-40 TO +105	•C
STORAGE TEMP.	-40 TO +105	•C
SOLDERING TEMP.	+260	•C
2.0mm FROM BODY	3	SEC. MAX.
* t<10µS		

NOTES:

- 1. ONLY ONE BIN CODE PER TUBE IS ALLOWED.
- 2. ONLY FULL TUBES ARE ACCEPTABLE.



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.00}$



-7.62 [0.300]-

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

0.39" 1 DIGIT, 7 SGMT, LED DISPLAY, 590nm YELLOW CHIPS, GRAY FACE W/WHTE SGMTS, COMMON ANODE, 10 PINS

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

UNCONTROLLED DOCUMENT DATE: 08.29.11 DRAWN BY: AΒ PAGE: 1 OF 1 CHKD BY: JD SCALE: NTS APRVD BY: JD (Pb) UNIT: mm [INCH]