



# UNCONTROLLED DOCUMENT


## CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.











## PART NUMBER


# IDS-C412BI-UPG

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C  $I_f = 10 \text{mA}$ PARAMETER MIN TYP MAX UNITS TEST COND PEAK WAVELENGTH 525 nm FORWARD VOLTAGE 3.5 4.0 ٧f REVERSE VOLTAGE 5.0  $V_r$  $I_r=100\mu A$ AXIAL INTENSITY 7000 μcd If=10mA EMITTED COLOR: GREEN FACE COLOR: GRAY SEGMENT COLOR: MILKY WHITE DIFFUSED

### LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/'C
OPERATING, STORAGE TEMP.	-40  TO  +85	<b>.</b> C
SOLDERING TEMP.	+ 260	°C
2.0mm FROM BODY		3 SEC. MAX
<del></del>		

\* t<10µS



\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION -0.000

REV.

## PART NUMBER LDS-C412BI-UPG

0.43" SINGLE DIGIT, SEVEN SEGMENT DISPLAY. 525nm GREEN CHIPS, GRAY FACE WITH WHITE SEGMENTS, COMMON CATHODE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY:

APPROVED BY:

DATE: 6.5.03 PAGE: 1 OF 1 SCALE: N/A

CHECKED BY: