











PART NUMBER	LDS-CA12RI-UPG		А	
DATE	DATE E.C.N. NUMBER AND REVISION COMMENTS			
03.06.13	E.C.N. #10BRDR. & REDRAWN.		Α	

Α

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=10mA					
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		525		nm	_
FORWARD VOLTAGE *		7.0/3.5	8.0/4.0	V_{f}	
REVERSE VOLTAGE	5.0			V_r	Ir=100µA
AXIAL INTENSITY		9000		μcd	$I_f = 10mA$
EMITTED COLOR:	GREEN				
FACE COLOR:	GRAY				
SEGMENT COLOR: MILKY WHITE DIFFUSED					

* SECOND VALUE FOR SINGLE CHIP IN DECIMAL POINT.

LIMITS OF SAFE OPERATION AT 25°C	PER CHIP	
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	120	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	. C
SOLDERING TEMP.	+ 260	. C
2.0mm FROM BODY		3 SEC. MAX

PAGE:

SCALE:

UNIT:

OF

NTS

mm [INCH]

CHKD BY:

APRVD BY:

KF

KF

* t<10µS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ±DECIMAL PRECISION MAX.=±0.000 UNCONTROLLED DOCUMENT

1.0" SINGLE DIGIT SEVEN SEGMENT DISPLAY,525nm GREEN CHIPS,GRAY FACE WITH WHITE SEG,COMMON CATHODE. DATE: 03.06.13 DRAWN BY: MA



Creating LED and LCD Solutions Together