



PART NUMBER	LDS-SMA5624RI-SITR	REV	A

REV	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	ECN-Lumex202600035	10.28.26











POLARITY



RECOMMENDED SOLDER PAD LAYOUT



ELECTRO-OPTICAL CHARACTERISTIC TA=25℃ PER SEGMENT

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGHT	-	640	-	nm	If=20mA
FORWARD VOLTAGE	-	2.0	2.4	Vf	If=20mA
REVERSE CURRENT	-	-	10	uA	V_R=5V
LUMINOUS INTENSITY	-	25000	-	ucd	If=20mA
EMITTED COLOR	RED				
FONT COLOR	GRAY				
SEGMENT COLOR	MILKY WHITE DIFFUSED				

ABSOLUTE MAXIMUM RATINGS TA=25℃ PER SEGMENT

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	40	mA
FORWARD CURRENT	20	mA
POWER DISIPATION	50	mW
REVERSE VOLTAGE	5	V
STORAGE TEMPERATURE	-40 TO +105	℃
OPERATING TEMPERATURE	-40 TO +105	℃

*1/10 DUTY,1KHz

MOISTURE SENSITIVE DEVICE
PER JEDEC LEVEL 2a STANDARDS

STATIC DEVICE FOLLOW PROPER
E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+\text{DECIMAL PRECISION}}_{-0.00}$ MAX.= $^{+0.00}_{-\text{DECIMAL PRECISION}}$

ITW LUMEX
Creating LED - LCD & Switch Solutions
2325. KENYON ROAD.
BARTLETT, IL 60103.
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

20.0(L)*12.5(W)*2.1(H)mm, 0.56" SINGLE SEVEN SEGMENT DISPLAY, RED COLOR, GRAY FACE WITH WHITE SEGMENTS, COMMON ANODE, TAPE & REEL.


****THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE.****

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.


DATE : 2026.10.28	DRAWN BY : E.C.
PAGE : 1 OF 2	CHKD BY : T.S.
SCALE : NTF	APRVD BY : G.Y.
UNIT : mm [INCH]	Pb

PART NUMBER	LDS-SMA5624RI-SITR	REV	A


PROFILE



CARRIER TAPE DIMENSION



***SECTION** B-B*



***SECTION** A-A*

NOTE:
1. 1300 PCS/REEL

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+\text{DECIMAL PRECISION}}_{-0.00}$ MAX.= $^{+0.00}_{-\text{DECIMAL PRECISION}}$

ITW LUMEX
Creating LED · LCD & Switch Solutions

2325. KENYON ROAD.
BARTLETT, IL 60103.
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

20.0(L)*12.5(W)*2.1(H)mm, 0.56" SINGLE SEVEN SEGMENT DISPLAY, RED COLOR, GRAY FACE WITH WHITE SEGMENTS, COMMON ANODE, TAPE & REEL.

****THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE.****

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE : 2026.10.28	DRAWN BY : E.C.
PAGE : 2 OF 2	CHKD BY : T.S.
SCALE : NTF	APRVD BY : G.Y.
UNIT : mm [INCH]	Pb