



PART NUMBER	LDS-SMA5629RI-UWTR	REV	A

REV	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	ECN-Lumex202600036	10.28.26











POLARITY



RECOMMENDED SOLDER PAD LAYOUT



ELECTRO-OPTICAL CHARACTERISTIC TA=25℃ PER SEGMENT

PARAMETER		MIN	TYP	MAX	UNITS	TEST COND
CHROMATICITY COORDINATE	X	-	0.285	-	-	If=5mA
	Y	-	0.275	-	-	
FORWARD VOLTAGE		-	2.9	3.2	Vf	If=5mA
REVERSE CURRENT		-	-	10	uA	V_R=5V
LUMINOUS INTENSITY		-	50000	-	ucd	If=5mA
EMITTED COLOR		WHITE				
FONT COLOR		GRAY				
SEGMENT COLOR		MILKY WHITE DIFFUSED				

ABSOLUTE MAXIMUM RATINGS TA=25℃ PER SEGMENT

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	60	mA
FORWARD CURRENT	10	mA
POWER DISIPATION	33	mW
REVERSE VOLTAGE	5	V
STORAGE TEMPERATURE	-40 TO +100	℃
OPERATING TEMPERATURE	-40 TO +85	℃

*1/10 DUTY,1KHz

MOISTURE SENSITIVE DEVICE
PER JEDEC LEVEL 2a STANDARDS

STATIC DEVICE FOLLOW PROPER
E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+\text{DECIMAL PRECISION}}_{-0.00}$ MAX.= $^{+0.00}_{-\text{DECIMAL PRECISION}}$

ITW LUMEX
Creating LED - LCD & Switch Solutions
2325. KENYON ROAD.
BARTLETT, IL 60103.
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

20.0(L)*12.5(W)*2.1(H)mm, 0.56" SINGLE SEVEN SEGMENT DISPLAY, WHITE COLOR, GRAY FACE WITH WHITE SEGMENTS, COMMON ANODE, TAPE & REEL.


****THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE.****

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.


DATE : 2026.10.28	DRAWN BY : E.C.
PAGE : 1 OF 2	CHKD BY : T.S.
SCALE : NTF	APRVD BY : G.Y.
UNIT : mm [INCH]	Pb

PART NUMBER	LDS-SMA5629RI-UWTR	REV	A


PROFILE



CARRIER TAPE DIMENSION



***SECTION** B-B*



***SECTION** A-A*

NOTE:
1. 1300 PCS/REEL

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+\text{DECIMAL PRECISION}}_{-0.00}$ MAX.= $^{+0.00}_{-\text{DECIMAL PRECISION}}$

ITW LUMEX
Creating LED · LCD & Switch Solutions

2325. KENYON ROAD.
BARTLETT, IL 60103.
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

20.0(L)*12.5(W)*2.1(H)mm, 0.56" SINGLE SEVEN SEGMENT DISPLAY, WHITE COLOR, GRAY FACE WITH WHITE SEGMENTS, COMMON ANODE, TAPE & REEL.

****THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE.****

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE : 2026.10.28	DRAWN BY : E.C.
PAGE : 2 OF 2	CHKD BY : T.S.
SCALE : NTF	APRVD BY : G.Y.
UNIT : mm [INCH]	Pb