UNCONTROLLED DOCUMENT PART NUMBER REV. LLP-C20662S - 50.50 [1.988] -- 0.40 [0.016] - 1.10 [0.043] R3.53 [R0.139] 1.20 [0.047] R3.13 [R0.123] NOTES: 1. MATERIAL: CLEAR PC 2. TOP SURFACE TEXTURED DIFFUSED. 3. BOTTOM SURFACE IS SMOOTH FINISH. *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECINAL PRECISION MAX.= +0.000 (±0.000), XXX=±0.127 (±0.000), XXX=±0.127 (±0.000). 290 E. HELEN ROAD PALATINE, IL 60067-6976 CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DIDCUMENT IS THE PROPERTY OF PART NUMBER REV. LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUNEX PHONE: +1.847.359.2790 LLP-C20662S INC., THE HOLDER OF THIS DESCUMENT SHALL KEEP ALL INFORMATION US WEB: www.lumex.com contained Herein Confidential and shall protect same in whole or IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. TW WEB: www.lumex.com.tw RELIABILITY NOTE
OUR NANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT CHECKED BY: APPROVED BY: DATE: 11.05.04 DRAWN BY: LIGHT PIPE, PAGE: 1 ÖF 1 SOLDER HEAT IS A NAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS. SCALE: N/A JD