PART NUMBER REV. LLP-LXC080302D-44 UNCONTROLLED DOCUMENT E.C.N. NUMBER AND REVISION COMMENTS DATE 41.00 [1.614] -6.50 [0.256] -Ø3.00 [0.118] 4.00 [0.157] (8 PLS.) (7 PLS.) 35.40 [1.394] 43.80 [1.724] 0.70 [0.028] 8.40 (0.331) **—** 1.70 [0.067] SECTION A-A 1.40 [0.055] (2 PLS.) 0.80 [0.031] (2 PLS.) NOTES: 3.80 [0.150] 40.00 [1.575] 1. MATERIAL: CLEAR POLYCARBONATE UL94V-0. (LIGHT PIPES) 2. MATERIAL: BLACK NORYL, UL94V-0. (HOLDER) 3. TEMP. RANGE: -60°C TO +125°C. 38.40 [1.512] — 4. RECOMMENDED LED: SSL-LX3054Txx SERIES. 36.80 [1.449] PCB LAYOUT 2.00 [0.079] 6.80 [0.268] 36.00 [1.417] -(2 PLS.) 2.73 [0.107] 4.60 [0.181] (2 PLS.) ø3.40 [ø0.134] 2.54 [0.100] (8 PLS.) 4.80 [0.189] (8 PLS.) 3.85 [0.152] 0 00 00 00 00 00 00 Ø0.92 [Ø0.036] 1.46 [0.057] (16 PLS.) (7 PLS.) \*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010") CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX 290 E. HELLEN ROAD PART NUMBER REV. PALATINE, ILLINOIS 60067 PHONE: 1-847-359-2790 LLP-LXC080302D-44 INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION INCORPORATED WEB: HTTP://WWW.LUMEX.COM CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. APPROVED BY: DATE: 1-19-98 CHECKED BY: DRAWN BY:

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE

THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

DU

PAGE:

SCALE:

1 OF 1

N/A

3mm ROUND, 8 UNIT DISCRETE LED ARRAY LIGHT PIPE.