

UNCONTROLLED DOCUMENT


PART NUMBER

LPF-R013425SD-22

REV.

D

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #11054.	11.12.03
B	E.C.N. #11087.	1.28.04
C	E.C.N. #11115.	4.1.04
D	E.C.N. #11151.	7.13.04



NOTES:

1. MATERIAL: CLEAR PC.
2. (356534) TO APPEAR ON SURFACE.
3. ENDS TO BE TEXTURE DIFFUSED.
4. FLAMMABILITY RATING: UL 94V-0

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -0.00

REV.

D

PART NUMBER

LPF-R013425SD-22

CUSTOM 3 POSITION LIGHT PIPE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

BC

CHECKED BY:

APPROVED BY:

DATE: 9.5.03

PAGE: 1 OF 1

SCALE: N/A