UNCONTROLLED DOCUMENT *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: $X=\pm 1$ (± 0.039), $X.X=\pm 0.5$ (± 0.020), $X.XX=\pm 0.25$ (± 0.010), $X.XXX=\pm 0.127$ (± 0.005). LEAD SIZE= ± 0.05 (± 0.002), LEAD LENGTH= ± 0.75 (± 0.030). MIN= ± 0.000 MIN= ± 0.0000 MIN= Creating LED and LCD Solutions Together™ 40.64 [1.600] -3.20 [0.126] 9.60 [0.378]-2.26 [0.089]-6.35 [0.250] (3 PLS.) 3.55 [0.140] (6 PLS.) 13.98 [0.550] 4.20 [0.165] 29.60 [1.165]-SECTION A-A -2.26 [0.089] +8.10 [0.319] +7.00 [0.276] DETAIL-A -1.30 [0.051] -R3.77 [R0.148] -3.75 [0.148] 1.00 [0.039] 2.00 [0.079]— -R15.00 [R0.591] -R18.00 [R0.709] 1.50 [0.059]---2.00 [0.079]--> 82.85 [3.262]-51.38 [2.023] 31.20 [1.228]-THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LIMEX INC. THE PROTECT AS SPECIFICALLY MITHORIZED IN WRITING BY LIMEX INC., THE HOLDER OF THIS DOCUMENT SHALL REPORT AS TREEFFALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. 0.90 [0.035]—— 1.00 [0.039]—— 6.35 [0.250] (3 PLS.) √0.15 [0.006] @ 45 (2 PLS.) -1.00 [0.039] **THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.** -2.00 [0.079] 7.62 [0.300] (2 PLS.) 5.00 [0.197] (6 PLS.) 39.29 [1.547] CUSTOM LIGHT PIPE. PART NUMBER 01.06.16 DETAIL-A **B** -ø2.79 [ø0.109] #11980 #11915. - ø1.93 [ø0.075] **B** E.C.N. NUMBER AND REVISION LPF-R061252S, *DIFFUSED FACES UNIT: DATE: SCALE: PAGE: UNCONTROLLED DOCUMENT MATERIAL: CLEAR POLYCARBONATE, UL 94V-0.
RECOMMENDED PCB HOLE DIAMETER: Ø2.8mm±0.1. NOTES: mm [INCH] 10.16.13 NTS 유 COMMENTS CHKD BY: DRAWN BY: APRVD BY: REV. Z

M

죾 Р