






UNCONTROLLED DOCUMENT



TIMING DIAGRAM

PIN OUT		
PIN NO.	PIN NAME	FUNCTION
1	GND	GND TERMINAL
2	SDI	SERIAL DATA INPUT
3	CLK	CLOCK INPUT
4	/LE	LATCH INPUT
5~12	OUT 0~7	OUTPUT
13	/OE	OUTPUT ENABLE
14	SDO	SERIAL DATA OUTPUT
15	R-EXT	CONSTANT CURRENT PROG.
16	VDD	5V SUPPLY



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005).

PART NUMBER		REV.
LSD-LXS0816SDIP		A
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #11148.	01.24.07

ELECTRICAL CHARACTERISTICS $T_A=25^\circ\text{C}$

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
INPUT VOLTAGE "H"	V_{IH}		0.7 V_{DD}		V_{DD}	V
INPUT VOLTAGE "L"	V_{IL}		GND		0.3 V_{DD}	V
OUTPUT LEAKAGE	I_{OH}	$V_{OH}=17.0\text{V}$			10	μA
OUTPUT VOLTAGE	V_{OL}	$I_{OL}=+1.0\text{mA}$			0.4	V
SERIAL OUT	V_{OH}	$I_{OH}=-1.0\text{mA}$				V
OUTPUT CURRENT 1	I_{OL1}	$V_{CE}=0.8\text{V}$, $R_{EXT}=865\Omega$		40		mA
CURRENT SKEW	dI_{OL1}		±1.5	±6.0		%
OUTPUT CURRENT 2	I_{OL2}	$V_{CE}=1.2\text{V}$, $R_{EXT}=330\Omega$		80		mA
CURRENT SKEW	dI_{OL2}		±1.5	±6.0		%
PULL-UP RESISTOR	$R_{IN(UP)}$		150	300	600	$K\Omega$
PULL-DOWN RESISTOR	$R_{IN(DOWN)}$		85	200	400	$K\Omega$
SUPPLY CURRENT						
OUTPUTS "OFF"	$I_{DD(off)1}$	$R_{EXT}=OPEN$		0.1	1.0	mA
	$I_{DD(off)2}$	$R_{EXT}=865\Omega$	0.1	0.2	1.0	mA
	$I_{DD(off)3}$	$R_{EXT}=330\Omega$	0.1	0.2	1.0	mA
OUTPUTS "ON"	$I_{DD(on)1}$	$R_{EXT}=865\Omega$	7.0	12.0	18.0	mA
	$I_{DD(on)2}$	$R_{EXT}=330\Omega$	10.0	22.0	32.0	mA

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
SUPPLY VOLTAGE	0~+7.0	V
OUTPUT VOLTAGE	-0.5~+17.0	V
OUTPUT CURRENT	+90	mA
INPUT VOLTAGE	-0.4~ $V_{DD}+0.4$	V
GND TERMINAL CURRENT	720	mA
CLOCK FREQUENCY	20	MHz
POWER DISSIPATION	+0.78	W
OPERATING TEMPERATURE	-40 TO +85	$^\circ\text{C}$
STORAGE TEMPERATURE	-55 TO +150	$^\circ\text{C}$



UNCONTROLLED DOCUMENT

REV.

A

PART NUMBER

LSD-LXS0816SDIP

8-BIT CONSTANT CURRENT LED SINK DRIVER,
16 PIN DIP PACKAGE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JC

CHECKED BY:


APPROVED BY:

DATE: 2.12.02

PAGE: 1 OF 2

SCALE: N/A

UNCONTROLLED DOCUMENT



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005), LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN= +0.00 PRECISION -0.00, MAX.= +0.00 -0.00 PRECISION


PART NUMBER		REV.
LSD-LXS0816SDIP		A
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	SEE PAGE 1	

SWITCHING CHARACTERISTICS $T_A=25^\circ\text{C}$

PARAMETER		MIN	TYP	MAX	UNIT
PROPAGATION DELAY TIME {L ~ H}	INn-OUTn		200	300	nS
	/LE-OUTn		200	300	nS
	/OE-OUTn		200	300	nS
	CLK-SQUT		50	70	nS
PROPAGATION DELAY TIME {H ~ L}	INn-OUTn		200	300	nS
	/LE-OUTn		200	300	nS
	/OE-OUTn		200	300	nS
	CLK-SQUT		50	70	nS
PULSE WIDTH	CLK	15		20	nS
	/LE	20		30	nS
SET-UP TIME FOR LATCH		10		20	nS
HOLD TIME EFOR LATCH		10		25	nS
MAX CLK RISE TIME				5	nS
MAX CLK FALL TIME				5	nS
OUTPUT RISE TIME			150	200	nS
OUTPUT FALL TIME			150	200	nS

* TEST CONDITIONS: $V_{DD}=5.0V$, $V_{CE}=0.8V$, $V_{IH}=V_{DD}$, $V_{IL}=GND$, $REXT=865\Omega$, $I_{OUT}=40mA$, $V_L=3.4V$, $R_L=65\Omega$, $C_L=10.5pF$

8 BIT LED DRIVER REXT-IOUT (BLACK)



UNCONTROLLED DOCUMENT

REV.	PART NUMBER
A	LSD-LXS0816SDIP

8-BIT CONSTANT CURRENT LED SINK DRIVER,
16 PIN DIP PACKAGE.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX We Turn Problems In Work For You		290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw	
DRAWN BY: JC	CHECKED BY:	APPROVED BY:	DATE: 2.12.02 PAGE: 2 OF 2 SCALE: N/A