





UNCONTROLLED DOCUMENT



NOTES:

1. ANODE
2. CATHODE
3. NC
4. MAIN TERMINAL
5. SUBSTRATE
DO NOT CONNECT
6. MAIN TERMINAL



ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
I FORWARD VOLTAGE	V _F	I _F =10mA	-	1.2	1.5	V
REVERSE CURRENT	I _R	V _R =4V	-	-	10	μA
O PEAK BLOCKING CURRENT	I _{DRM}	V _{DRM} =RATED	-	60	500	nA
ON STATE VOLTAGE	V _{TM}	I _{TM} =100mA	-	1.8	3	V
RISE RATE (OFF STATE)	dV/dT		100	-	-	V/μS
T HOLDING CURRENT	I _H		-	100	-	μA
INHIBIT VOLTAGE (MT1 - MT2)	V _{INH}	I _F =10mA	-	5.0	20	V
INHIBIT STATE LEAKAGE	I _{DM2}	I _F =RATED I _{IT} , RATED V _{DRM} , OFF STATE	-	-	500	μA
ISOLATION RESISTANCE	R _{ISO}	500V D.C.	5 ¹⁰	10 ¹¹	-	Ω
MIN TRIGGER CURRENT	I _{IT}	MAIN TERMINAL=3V	-	-	5	mA

I=INPUT, O=OUTPUT, T=TRANSFER CHARACTERISTICS.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=+DECIMAL PRECISION -0.00, MAX.=+0.00 -DECIMAL PRECISION

REV.

A

PART NUMBER

OCP-PCTR126-400V

SIX PIN DIP SINGLE CHANNEL 400V PHOTOCOUPLER,
ZERO CROSSING TRIAC.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JC

CHECKED BY:

APPROVED BY:

DATE: 7.12.01

PAGE: 1 OF 1

SCALE: N/A

PART NUMBER

OCP-PCTR126-400V

REV.

A

REV. E.C.N. NUMBER AND REVISION COMMENTS

A E.C.N. #11148.

DATE

5.16.07

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

PARAMETER	SYMBOL	MAX	UNITS
I FORWARD CURRENT	I _F	50	mA
PEAK FORWARD CURRENT	I _{FM}	1	A
REVERSE VOLTAGE	V _R	6	V
POWER DISSIPATION	P _D	70	mW
O OFF-STATE OUTPUT TERMINAL VOLTAGE	V _{DRM}	400	V
PEAK REPETITIVE SURGET CURRENT	I _{TSM}	1	A
POWER DISSIPATION	P _D	300	mW
TOTAL POWER DISSIPATION	P _{tot}	330	mW
ISOLATION VOLTAGE 1 MIN.	V _{ISO}	5000	V _{RMS}
OPERATING TEMPERATURE	T _{opr}	-40 TO +80	°C
STORAGE TEMPERATURE	T _{stg}	-40 TO +125	°C
SOLDERING TEMPERATURE	T _{sol}	+260	°C
2.0mm FROM BODY		10 SEC. MAX	

I=INPUT, O=OUTPUT.



UNCONTROLLED DOCUMENT