







UNCONTROLLED DOCUMENT



NOTES:

1. PARTS SUPPLIED ON TAPE AND REEL.

PART NUMBER
OED-HPI-30REV.
B

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10BRDR.	12.31.97
B	E.C.N. #10BRDR. & REDRAWN IN 3D.	5.30.03

ELECTRO-OPTICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH SENS.		880		nm	
SPECTRAL SENSITIVITY	500		1000	nm	
OPEN CIRCUIT VOLTAGE		0.38		V	$E_e = 0.10 \text{ mW/cm}^2$
SHORT CIRCUIT CURRENT		35		μA	$E_e = 0.10 \text{ mW/cm}^2$
DARK CURRENT			30	nA	$V_r = 10\text{V}$
SWITCHING TIME		45		nS	$V_r = 10\text{V}, R_L = 1000\Omega$
TOTAL CAPACITANCE			30	pF	$E_e = 0.0 \text{ mW/cm}^2$
HALF ANGLE		± 80		degrees	$V_r = 3\text{V}, F = 1\text{MHz}$
EPOXY FINISH:	WATER CLEAR				

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
REVERSE VOLTAGE	30	V
POWER DISSIPATION	200	mW
OPERATING TEMP.	-25 TO +80	$^\circ\text{C}$
STORAGE TEMP.	-25 TO +120	$^\circ\text{C}$

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.038), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX= +0.00 -DECIMAL PRECISION

REV.
BPART NUMBER
OED-HPI-30CERAMIC SURFACE MOUNT
PIN PHOTO DIODE.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 2.8.95

BC

PAGE: 1 OF 1

SCALE: N/A

UNCONTROLLED DOCUMENT