



UNCONTROLLED DOCUMENT

PART NUMBER
OED-LXR44ST-TR


REV.

ELECTRO-OPTICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$


PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
COLLECTOR DARK CURRENT	I_{ced}	$V_{ce} = 10\text{V}$ $E_e = 0\text{mw/cm}^2$			100	nA
COLLECTOR LIGHT CURRENT	I_c	$V_{ce} = 5\text{V}$ $E_e = 1.0\text{mw/cm}^2$		0.3		mA
COLLECTOR-EMITTER SATURATION VOLTAGE	$V_{ce(sat)}$	$I_c = 0.5\text{mA}$ $E_e = 1\text{mw/cm}^2$		0.8		V
SWITCHING SPEEDS:		$V_r = 10\text{V}$				
RISING TIME	T_r			6.0		μS
FALLING TIME	T_f	$R_l = 1000\Omega$		6.0		μS
SPECTRAL SENSITIVITY	λ			730~1100		nm
PEAK WAVELENGTH	λ_p			940		nm
ANGULAR RESPONSE	$\Delta\theta$			± 45		DEG
LENS COLOR:				BLACK		

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
COLLECTOR-EMITTER VOLTAGE	30	V
EMITTER-COLLECTOR VOLTAGE	5	V
POWER DISSIPATION	150	mW
OPERATING TEMP.	-40 TO +100	$^\circ\text{C}$
STORAGE TEMP.	-40 TO +100	$^\circ\text{C}$
SOLDERING TEMP.	+260	$^\circ\text{C}$
2.0mm FROM BODY		5 SEC. MAX



RECOMMENDED SOLDER PAD LAYOUT



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN=+DECIMAL PRECISION -0.00, MAX.=+0.00 -DECIMAL PRECISION

REV.

PART NUMBER

OED-LXR44ST-TR

RIGHT ANGLE BOOMERANG SURFACE MOUNT
PHOTO TRANSISTOR, BLACK LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JD

CHECKED BY:

APPROVED BY:

DATE: 6.19.06

PAGE: 1 OF 1

SCALE: N/A