








UNCONTROLLED DOCUMENT



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION -0.00, MAX.= +0.00 -DECIMAL PRECISION

PART NUMBER
OED-RM200-1

REV.
D

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10203.	7-3-96
B	E.C.N. #10445. & REDRAWN.	7-23-98
C	E.C.N. #10579.	1-10-00
D	E.C.N. #10614	4-14-00

ELECTRO-OPTICAL CHARACTERISTICS T_A=25°C

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
SUPPLY VOLTAGE	V _{cc}		5		V
SUPPLY CURRENT	I _{cc}	-	-	3	mA
DETECTING DISTANCE	L	10	-	-	m
HALF ANGLE	θ	-	±45	-	DEG
B.P.F. CENTER FREQUENCY	f _o	-	40	-	KHz
PEAK WAVELENGTH	p	-	940	-	nm
HIGH LEVEL OUTPUT VOLT.	V _{oh}	V _{cc}	-	-	V
LOW LEVEL OUTPUT VOLT.	V _{ol}	-	-	0.45	V
HIGH/LOW LVL. PULSE WIDTH	T _H /T _L	440	-	770	μS

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	UNITS	RATING	UNITS
SUPPLY VOLTAGE	V _{cc}	6.3	V
SUPPLY CURRENT	I _{cc}	3	mA
OUTPUT VOLTAGE	V _{out}	6.3	V
OPERATING TEMP.	T _{opr}	-10 TO +60	°C
STORAGE TEMP.	T _{str}	-20 TO +75	°C
SOLDERING TEMP.	T _{sol}	+260	°C
2.0mm FROM BODY		3	SEC. MAX

UNCONTROLLED DOCUMENT

REV.
D

PART NUMBER
OED-RM200-1

REMOTE CONTROL RECEIVER MODULE.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX
INCORPORATED

290 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
PHONE: (847) 359-2790
WEB: <http://www.lumex.com>

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 10-9-95
TM/BC			PAGE: 1 OF 1
			SCALE: N/A