




UNCONTROLLED DOCUMENT

PART NUMBER
OED-ST-1L1R2REV.
D

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10150.	4.19.96
B	E.C.N. #10360.	2.6.97
C	E.C.N. #10BRDR.	1.5.98
D	E.C.N. #10853 & #10BRDR.	4.19.02

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
COLLECTOR DARK CURRENT			100	nA	$V_{ce0} = 10\text{V}$ $E_e=0\text{mW/cm}^2$
COLLECTOR LIGHT CURRENT	4.0	15.0		mA	$V_{ce} = 3\text{V}$ $E_v = 1000\text{ LUX}$
COLLECTOR-EMITTER SATURATION VOLTAGE			0.4	V	$I_c=0.2\text{mA}$ $E_v=1000\text{ LUX}$
SWITCHING SPEEDS					$V_{cc} = 10\text{V}$
RISE TIME		2.5		μS	$I_c = 1\text{mA}$
FALL TIME		3.8		μS	$R_L = 100\Omega$
PEAK WAVELENGTH		880		nm	
SPECTRAL SENSITIVITY	700		1050	nm	
ANGULAR RESPONSE		± 10			
LENS COLOR:	BLACK				

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
COLLECTOR-EMITTER VOLTAGE (V_{ce0})	20	V
EMITTER-COLLECTOR VOLTAGE (V_{ce0})	5	V
POWER DISSIPATION	100	mW
OPERATING TEMPERATURE	-20 TO +80	$^\circ\text{C}$
STORAGE TEMPERATURE	-30 TO +85	$^\circ\text{C}$
SOLDERING TEMP.	+260	$^\circ\text{C}$
2.0mm FROM BODY	3 SEC. MAX	

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV.
DPART NUMBER
OED-ST-1L1R2

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw



T-5mm PHOTOTRANSISTOR,
WATER CLEAR LENS, WITH DAYLIGHT FILTER.

DRAWN BY: GB	CHECKED BY:	APPROVED BY:	DATE: 1.5.98
			PAGE: 1 OF 1
			SCALE: N/A

GB