

SA58M— ① ② ③ ④ ⑤ — ⑥

SWITCH FUNCTION CODE	SWITCH FUNCTION DESCRIPTION
2	MECHANICAL, MAINTAIN, SOLDER TERMINAL
B	MECHANICAL, MAINTAIN, NO/NO WIRELEADS
D	MECHANICAL, MAINTAIN, NC/NC WIRELEADS
F	MECHANICAL, MAINTAIN, NO/NC WIRELEADS

HOUSING MATERIAL CODE	HOUSING DESCRIPTION
1	STAINLESS STEEL
2	ALUMINUM, INHERENT

HOUSING ADAPTATION	BUTTON TYPE CODE	BUTTON DESCRIPTION
STAINLESS STEEL & ALUMINUM INHERENT HOUSING	0	NON.—ILLUMINATION
	2	RING ILLUMINATION
	3	POWER/STANDBY ILLUMINATION
ALUMINUM INHERENT HOUSING	R	RED BUTTON, ONLY FOR NON—ILLUMINATION
	G	GREEN BUTTON, ONLY FOR NON—ILLUMINATION
	Y	YELLOW BUTTON, ONLY FOR NON—ILLUMINATION
	B	BLUE BUTTON, ONLY FOR NON—ILLUMINATION
	D	GOLD BUTTON, ONLY FOR NON—ILLUMINATION

LED COLOR CODE	LED COLOR
N	NONE
R	RED
B	BLUE
G	GREEN
Y	YELLOW
W	WHITE

LED INLET VOLTAGE CODE		LED INLET VOLTAGE
NON— WIRELEADS	IF BLANK*	FOLLOW LED SPECIFICATION
	IF BLANK*	FOLLOW LED SPECIFICATION
WIRELEADS	05	5V
	12	12V
	24	24V

ANY CODE	DESCRIPTION
IF BLANK*	NA
XXX	PER CUSTOMER SPECIAL REQUEST

MECHANICAL CHARACTERISTICS:

SWITCH CIRCUITRY: SPDT-DB
SWITCH ACTION: MAINTAINED (PER CHART)
PRE-TRAVEL: 1.27 mm NOMINAL
OVER-TRAVEL: 0.254 mm NOMINAL
TOTAL TRAVEL: 1.524 mm NOMINAL
OPERATING FORCE: 525 g [5.15N] NOMINAL
RELEASEING FORCE: 340 g NOMINAL
PANEL THICKNESS:0.5-4.5mm

CONTACTS: SILVER
NUT TORQUE FORCE: MAX 11.5 kgf*cm [10 LB*in]

ELECTRICAL LIFE:
MAINTAINED: 5A@28VDC 25KCYCLES NOMINAL.

ENVIROMENTAL SPECIFICATIONS:

OPERATING TEMPERATURE: -40° C to +85° C[-40° F to +185° F]
IP67 COMPLIANT


ELECTRICAL SPECIFICATIONS:

DIELECTRIC STRENGTH: 1,000VAC
INSULATION RESISTANCE: 1G OHM
CONTACT RESISTANCE:
50m /250m OHMS MAX INITIAL(NON-WIRELEAD / WIRELEADS)


LED SPECIFICATIONS:

SEE LED SPECIFICATION

CERTIFICATION: UL 61058




LED SPECIFICATION					
LED CODE	LED Color	CIRCUITRY	Vf(VDC)	If (mA)	
			Color		
R	RED		1.8 ~ 2.5	20	
B	BLUE		2.8 ~ 3.5	20	
G	GREEN		2.8 ~ 3.5	20	
Y	YELLOW		1.8 ~ 2.5	20	
W	WHITE		2.8 ~ 3.5	20	
Notes:					
1.) Lead Soldering Temperature (4mm above from Body) : 280°C for 5 seconds					
2.) Hand Soldering Temperature (4mm above from Body) : 320°C for 3 seconds					
WIRELEADS SPECIFICATION					
WIRELEADS TYPE	WIRELEADS SPECIFICATION	SW TERMINAL	SW TERMINAL	LED	
				COLOR	
		NO	NC	+	-
ILLUMINATION	AWG24 / UL1007	BLUE	YELLOW	RED	BLACK
NON-ILLUMINATION		BLUE	YELLOW	-	-




* NOTE:
1.SUPPLY HEX NUT AND SEALING WASHER BULK IN PACKED

THIS DOCUMENT IS THE INTELLECTUAL PROPERTY OF ITW ELECTRONIC BUSINESS ASIA CO., LIMITED AND MAY CONTAIN CONFIDENTIAL, PROPRIETARY, PRIVILEGED INFORMATION PROTECTED BY LAW. NEITHER THIS DOCUMENT NOR ANY INFORMATION IT CONTAINS CAN BE REPRODUCED, TRANSFORMED TO ANY OTHER FORMAT, OR DISTRIBUTED, WITHOUT WRITTEN PERMISSION BY ITW ELECTRONIC BUSINESS ASIA CO., LIMITED.
本文件為安天德百電股份有限公司之智慧財產，非經許可不得擷取、複製、轉變成其他形式使用或散佈

	Concept Drawing		Engineer Drawing	V	Sales Drawing
--	-----------------	--	------------------	---	---------------

RoHS Compliant		DIMENSION ARE IN MILLIMETERS			AN ILLINOIS TOOL WORKS COMPANY				
		TOLERANCES: UNLESS OTHERWISE NOTED 1 PLACE DECIMAL ± 0.5 2 PLACE DECIMAL ± 0.2 ANGULAR ±1°			DWG TITLE SA58M-MECHANICAL MAINTAIN, NONE/CENTER SPOT/ POWER STANDBY SYMBOL ILLUMINATION				
Yes	No	DATE 2017/12/12	REF: 58M-A,B			SIZE B	DWG NO.	SA58M-2,B,D,F	REV 3
		DRAWN K.Y.	REVIEW A.H.	APPROVED V.W.		SCALE : 3:2		SHEET 1 OF 3	



THIS DOCUMENT IS THE INTELLECTUAL PROPERTY OF ITW ELECTRONIC BUSINESS ASIA CO., LIMITED AND MAY CONTAIN CONFIDENTIAL, PROPRIETARY, PRIVILEGED INFORMATION PROTECTED BY LAW. NEITHER THIS DOCUMENT NOR ANY INFORMATION IT CONTAINS CAN BE REPRODUCED, TRANSFORMED TO ANY OTHER FORMAT, OR DISTRIBUTED, WITHOUT WRITTEN PERMISSION BY ITW ELECTRONIC BUSINESS ASIA CO., LIMITED.
本文件為安天德百電股份有限公司之智慧財產，非經許可不得擷取、複製、轉變成其他形式使用或散佈


	Concept Drawing		Engineer Drawing	V	Sales Drawing
--	-----------------	--	------------------	---	---------------

RoHS Compliant	
Yes	No
✓	

DIMENSION ARE IN MILLIMETERS			ITW Switches		
TOLERANCES: UNLESS OTHERWISE NOTED 1 PLACE DECIMAL ± 0.5 2 PLACE DECIMAL ± 0.2 ANGULAR ±1°			AN ILLINOIS TOOL WORKS COMPANY		
DATE 2017/12/12			DWG TITLE SA58M-MECHANICAL MAINTAIN. NONE/CENTER SPOT/ POWER STANDBY SYMBOL ILLUMINATION		
DRAWN <i>K.Y.</i>		REVIEW <i>A.H.</i>	APPROVED <i>V.W.</i>	SIZE B	DWG NO. SA58M-2,B,D,F
				THIRD ANGLE PROJECTION	REV 3
			SCALE : 3:2		SHEET 2 OF 3

REVISION RECORD

REV.	DESCRIPTION	DATE	DRAWN BY	DOCUMENT NO.
1	FOR SALES DRAWING	2018.12.12	K.Y.	DCN-201700063
2	ADDING ELECTRICAL SPECIFICATIONS	2018/3/21	K.Y.	DCN-201800048
3	ADDING UL 61058 CERTIFICATION	2018/5/31	K.Y.	DCN-201800067

RoHS Compliant		DIMENSION ARE IN MILLIMETERS			 AN ILLINOIS TOOL WORKS COMPANY			
		TOLERANCES: UNLESS OTHERWISE NOTED 1 PLACE DECIMAL ±0.5 2 PLACE DECIMAL ±0.2 ANGULAR ±1°			DWG TITLE SA58M-MECHANICAL MAINTAIN, NONE/CENTER SPOT/ POWER STANDBY SYMBOL ILLUMINATION			
Yes ✓	No	DATE 2017/12/12	REF: 58M- A, B	 THIRD ANGLE PROJECTION	SIZE A4	DWG NO.	SA58M-2,B,D,F	REV 3
		DRAWN <i>K.Y.</i>	REVIEW <i>a.h.</i>		APPROVED <i>v.w.</i>	SCALE : -	SHEET 3 OF 3	