






| PART NUMBER | SML-LX1206YW-TR                     | REV. | F    |
|-------------|-------------------------------------|------|------|
| DATE        | E.C.N. NUMBER AND REVISION COMMENTS |      | REV. |
| 03.14.03    | E.C.N. #10967.                      |      | A    |
| 01.20.05    | E.C.N. #11148                       |      | B    |
| 01.07.08    | E.C.N. #11466                       |      | C    |
| 03.09.09    | E.C.N. #11508                       |      | D    |
| 07.19.10    | E.C.N. #11644.                      |      | E    |
| 04.20.11    | E.C.N. #10BRDR. & REDRAWN.          |      | F    |



[C] RECOMMENDED SOLDER PAD LAYOUT



| ELECTRO-OPTICAL CHARACTERISTICS TA =25°C If=20mA |                      |      |     |          |           |
|--------------------------------------------------|----------------------|------|-----|----------|-----------|
| PARAMETER                                        | MIN                  | TYP. | MAX | UNITS    | TEST COND |
| PEAK WAVELENGTH                                  |                      | 585  |     | nm       |           |
| FORWARD VOLTAGE                                  |                      | 2.1  | 2.6 | Vf       | Ir=100μA  |
| REVERSE VOLTAGE                                  | 5.0                  |      |     | Vr       | If=20mA   |
| AXIAL INTENSITY                                  |                      | 6    |     | mcd      |           |
| VIEWING ANGLE                                    |                      | 160  |     | 2x theta |           |
| EMITTED COLOR:                                   | YELLOW               |      |     |          |           |
| EPOXY LENS FINISH:                               | MILKY WHITE DIFFUSED |      |     |          |           |

| [E] LIMITS OF SAFE OPERATION AT 25°C |            |       |
|--------------------------------------|------------|-------|
| PARAMETER                            | MAX        | UNITS |
| PEAK FORWARD CURRENT*                | 100        | mA    |
| STEADY CURRENT                       | 25         | mA    |
| POWER DISSIPATION                    | 65         | mW    |
| DERATE FROM 25°C                     | -1.2       | mW/°C |
| OPERATING TEMP.                      | -40 TO +85 | °C    |
| STORAGE TEMP.                        | -40 TO +85 | °C    |



\* t<10μS

|         |                                                                   |
|---------|-------------------------------------------------------------------|
| [D] [A] | CAUTION: MOISTURE SENSITIVE DEVICE<br>PER JEDEC LEVEL 2 STANDARDS |
|---------|-------------------------------------------------------------------|

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=<sup>+DECIMAL PRECISION</sup><sub>-0.00</sub> MAX.=<sup>+0.00</sup><sub>-DECIMAL PRECISION</sub>

UNCONTROLLED DOCUMENT

|                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                          |  |                 |              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------|--------------|
|  <p>290 E. HELEN ROAD<br/>PALATINE, IL 60067-6976<br/>PHONE: +1.847.359.2790<br/>FAX: +1.847.359.6538<br/>WEB: WWW.LUMEX.COM</p> | 3.2mm x 1.6mm PCB SURFACE MOUNT LED, 585nm YELLOW LED, MILKY WHITE DIFFUSED, TAPE & REEL.                                                                                                                                                                                                                                                                |  | DATE: 04.20.11  | DRAWN BY: AB |
|                                                                                                                                                                                                                    | **THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.**                                                                                                                                                                                                                                                |  | PAGE: 1 OF 2    | CHKD BY: KF  |
|                                                                                                                                                                                                                    | CONFIDENTIAL INFORMATION<br>THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. |  | SCALE: NTS      | APRVD BY: SS |
|                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                          |  | UNIT: mm [INCH] | (Pb)         |

NOTES:

1. THE CATHODE MARK IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=  $\begin{matrix} +0.00 \\ -0.00 \end{matrix}$  DECIMAL PRECISION MAX.=  $\begin{matrix} +0.00 \\ -0.00 \end{matrix}$  DECIMAL PRECISION

UNCONTROLLED DOCUMENT



290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
FAX: +1.847.359.6538  
WEB: WWW.LUMEX.COM

3.2mm x 1.6mm PCB SURFACE MOUNT LED, 585nm YELLOW LED, MILKY WHITE DIFFUSED, TAPE & REEL.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

|        |           |           |    |
|--------|-----------|-----------|----|
| DATE:  | 04.20.11  | DRAWN BY: | AB |
| PAGE:  | 2 OF 2    | CHKD BY:  | KF |
| SCALE: | NTS       | APRVD BY: | SS |
| UNIT:  | mm [INCH] |           | Ⓟ  |