


UNCONTROLLED DOCUMENT

ANODE ○──────── CATHODE







PART NUMBER

SML-LXFZ0603SYC/A3

E.C.N. NUMBER AND REVISION COMMENTS DATE E.C.N. #10967. 3,14,03

ELECTRO-OPTICAL CH	ARACTERIST	TICS TA=25'		$I_f = 20mA$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		590		nm	
FORWARD VOLTAGE		2.0	2.5	Vf	
REVERSE VOLTAGE	5.0			٧r	1 _r =100,uA
AXIAL INTENSITY		60		mcd	$I_f = 20mA$
VIEWING ANGLE		120		2x theta	
EMITTED COLOR:	YELLOW				
EPOXY LENS FINISH:	WATER CL	_EAR			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	160	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	60	mW
DERATE FROM 25°C	-0.67	mW/°C
OPERATING TEMP.	-40 TO +85	•C
STORAGE TEMP.	-40 TO +90	°C
# L 40 0		

* t<10µS

NOTES:

- 1. PARTS PACKAGED IN CONDUCTIVE COVER AND CARRIER TAPE.
- 2. THE CATHODE IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

CAUTION: MOISTURE SENSITIVE DEVICE PER JEDEC LEVEL 4 STANDARDS


						ļ		
			-) ($ \langle \langle \langle \langle \langle \langle \rangle \rangle \rangle $	1.75	[0.069]	<u> </u>	0.70
),315]	7		Ź <u>"</u>	<i>''</i>		3.50	[0.138]	
	/	Ⅲ	\ !!!!! !	100				

∠ Ø1.55 [Ø0.061]

2.00 [0.079]

TAPE FEED DIRECTION -

RECOMMENDED SOLDER PAD LAYOUT



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.001), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.001), X.XXX=±0.127 (±0.001), X

REV. PART NUMBER SML-LXFZ0603SYC/A3

4.00 [0.157] -

TOP TAPE

8.00 [0

0.8 x 1.6mm FLAT TOP SURFACE MOUNT, ULTRA THIN, 590nm SUPER YELLOW, 60 mcd. WATER CLEAR LENS. TAPE AND REEL.

LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



GB

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

APPROVED BY: DATE: DRAWN BY: CHECKED BY: 6.4.02 PAGE: 1 OF 1 SCALE: N/A