







| PART NUMBER | SML-LXL1206AC-TR                    | REV. | B    |
|-------------|-------------------------------------|------|------|
| DATE        | E.C.N. NUMBER AND REVISION COMMENTS |      | REV. |
| 05.26.10    | E.C.N. #11508.                      |      | A    |
| 10.12.10    | E.C.N. #11665.                      |      | B    |



## RECOMMENDED SOLDER PAD LAYOUT

ELECTRO-OPTICAL CHARACTERISTICS  $T_A = 25^\circ\text{C}$   $I_f = 20\text{mA}$ 

| PARAMETER          | MIN         | TYP | MAX | UNITS    | TEST COND              |
|--------------------|-------------|-----|-----|----------|------------------------|
| PEAK WAVELENGTH    |             | 605 |     | nm       |                        |
| FORWARD VOLTAGE    |             | 2.0 | 2.8 | $V_f$    |                        |
| REVERSE VOLTAGE    | 5.0         |     |     | $V_r$    | $I_r = 100\mu\text{A}$ |
| AXIAL INTENSITY    |             | 20  |     | mcd      | $I_f = 20\text{mA}$    |
| VIEWING ANGLE      |             | 60  |     | 2x theta |                        |
| EMITTED COLOR:     | AMBER       |     |     |          |                        |
| EPOXY LENS FINISH: | WATER CLEAR |     |     |          |                        |

LIMITS OF SAFE OPERATION AT  $25^\circ\text{C}$ 


| PARAMETER                      | MAX        | UNITS                |
|--------------------------------|------------|----------------------|
| PEAK FORWARD CURRENT*          | 160        | mA                   |
| STEADY CURRENT                 | 30         | mA                   |
| POWER DISSIPATION              | 100        | mW                   |
| DERATE FROM $25^\circ\text{C}$ | -1.2       | mW/ $^\circ\text{C}$ |
| OPERATING TEMP.                | -30 TO +85 | $^\circ\text{C}$     |
| STORAGE TEMP.                  | -40 TO +85 | $^\circ\text{C}$     |

\*  $t < 10\mu\text{s}$ 

CAUTION: MOISTURE SENSITIVE DEVICE  
PER JEDEC LEVEL 2 STANDARDS

## NOTES:

- THE CATHODE IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

LEAD FREE REFLOW PROFILE  
10 SEC. MAX.TOTAL TIME ABOVE  $220^\circ\text{C}$  IS 60 SECONDS MAX.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE:  $X = \pm 1$  ( $\pm 0.039$ ),  $X.X = \pm 0.5$  ( $\pm 0.020$ ),  $X.XX = \pm 0.25$  ( $\pm 0.010$ ),  $X.XXX = \pm 0.127$  ( $\pm 0.005$ ). LEAD SIZE =  $\pm 0.05$  ( $\pm 0.002$ ), LEAD LENGTH =  $\pm 0.75$  ( $\pm 0.030$ ). MIN = +DECIMAL PRECISION -0.00, MAX = +0.00 -DECIMAL PRECISION



290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
FAX: +1.847.359.6538  
WEB: WWW.LUMEX.COM

3.0mm x 1.6mm PCB SML WITH LENS, 605nm AMBER LED, WATER CLEAR LENS, TAPE AND REEL.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

|                 |              |
|-----------------|--------------|
| DATE: 02.22.05  | DRAWN BY: JD |
| PAGE: 1 OF 1    | CHKD BY: KF  |
| SCALE: N/A      | APRVD BY: SA |
| UNIT: mm [INCH] | (R)          |