



REV.









RECOMMENDED SOLDER PAD LAYOUT

ELECTRO-OPTICAL CHARACTERISTICS Tg=25°C If=20mA PARAMETER UNITS TEST COND PEAK WAVELENGTH nm FORWARD VOLTAGE Vf Ir=100µA REVERSE VOLTAGE ٧r 1100 AXIAL INTENSITY mcd lf=20mA VIEWING ANGLE 30 2x theta EMITTED COLOR: RED LENS FINISH: WATER CLEAR

LIMITS OF SAFE OPERATION AT 25°C		
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	60	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	60	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-40 TO +85	*C
STORAGE TEMP.	-40 TO +85	*C
* t<10uS		

CAUTION: MOISTURE SENSITIVE DEVICE PER JEDEC LEVEL 4 STANDARDS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+}$ DECIMAL PRECISION MAX.= $^{+}$ 0.00 PRECISION MAX.= $^{$

Creating LED and LCD Solutions Together™

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

WEB: WWW.LUMEX.COM

FAX: +1.847.359.6538

3.2mm x 2.4mm SURFACE MOUNT LED, 632nm SUPER INTENSITY RED, WATER CLEAR, TAPE & REEL.


THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.


ON	UNC	ON	/TR	OLL	ED	DOCL	IMENT
	DATE:	01	.09.	12	DRA	WN BY:	AB
	PAGE:	1	OF	2	CHK	(D BY:	DT
	SCALE:		NTS		APR	RVD BY:	KF
	UNIT: mm [INCH]				Pb		

REV.





TOTAL TIME ABOVE 220°C IS 60 SECONDS MAX.



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+DECIMAL}_{-0.00}$ PRECISION MAX.= $^{+0.00}_{-0.00}$ MAX.= $^{+$



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

3.2mm x 2.4mm SURFACE MOUNT LED, 632nm SUPER INTENSITY RED, WATER CLEAR, TAPE & REEL.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: PAGE:	01.09.12 2 OF 2	DRAWN BY: CHKD BY:	AB	
SCALE:	NTS	APRVD BY:	KF	
UNIT:	mm [INCH]	(Pb)		