
SML-LXL3535UPGCTR1

lm


2x theta


lf=350mA















RECOMMENDED SOLDER PAD LAYOUT



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.001), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD SIZE=±0.05 (±0.003). MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.003). MIN= +0.00 (±0.003). MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.003). MIN=

ELECTRO-OPTICAL CHARACTERISTICS Tg=25°C If=350mA MAX UNITS TEST COND PEAK WAVELENGTH 525 FORWARD VOLTAGE 2.7 3.3 If=350mA REVERSE VOLTAGE 5.0 ۷r lr=85mA

55

110

60

EMITTED COLOR: GREEN LENS FINISH: WATER CLEAR

42

AXIAL INTENSITY

VIEWING ANGLE

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	800	mA
STEADY CURRENT	500	mA
LED JUNCTION TEMP.	120	*C
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-40 TO +100	*C
STORAGE TEMP.	-40 TO +120	*C
* 1×10C		

* t<10µS

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

> CAUTION: MOISTURE SENSITIVE DEVICE PER JEDEC LEVEL 1 STANDARDS

Creating LED and LCD Solutions Together™

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

WEB: WWW.LUMEX.COM

3.5mm X 3.5mm TOP DOME SMT LED, GREEN, 1W.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

UNCONTROLLED DOCUMENT DATE: 03.25.13 DRAWN BY: MA PAGE: 1 OF 2 CHKD BY: DT


SCALE: NTS APRVD BY: DT UNIT: mm [INCH] (Pb)


PART NUMBER

SML-LXL3535UPGCTR1

REV.







*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.000}$ MAX.= $^{+0.000}_{-0.000}$ MAX.= $^{+0.00}_{-0.000}$ MAX.= $^{+0.000}_{-0.000}$ MAX.= $^{+0.000}_{-0.000}$ UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

3.5mm X 3.5mm TOP DOME SMT LED, GREEN, 1W.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DIVEDIVINOLLED DUCUMENT							
	DATE:	03.25.1	3	DRAWN BY:	MA		
	PAGE:	2 OF	2	CHKD BY:	DT		
	SCALE: NTS UNIT: mm [INCH]		APRVD BY:	DT			
			Pb				