




ELECTRO-OPTICAL CHARACTERISTIC TA=25°C

PARAMETER		MIN	TYP	MAX	UNITS	TEST COND
SUPPLY VOLTAGE	VDD	-	5	-	V	-
INPUT VOLTAGE(HIGH)	VIH	0.7VDD	-	VDD	V	-
INPUT VOLTAGE(LOW)	VIL	0	-	0.3VDD	V	-
PEAK WAVELENGTH (PER DOT)	R	-	630	-	nm	If=5mA
	G	-	520	-		
	B	-	470	-		
LUMINOUS INTENSITY (PER DOT)	R	72	-	180	mcd	If=5mA
	G	180	-	360		
	B	28.5	-	72		
POWER CONSUMPTION		-	-	1.8	W	-
VIEWING ANGLE (PER DOT)		-	120	-	2x theta1/2	If=5mA
EPOXY LENS FINISH		WATER CLEAR				

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ^{+DECIMAL PRECISION}_{-0.00} MAX= ^{+0.00}_{-DECIMAL PRECISION}



425 N. GARY AVE.
CAROL STREAM, IL 60188
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

ez RING SERIES, Ø37(Ø27)*2.3, 24 DOT RGB LEDs, DC 5V.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE : 2018.10.04

DRAWN BY : C.C.

PAGE : 1 OF 3

CHKD BY : E.C.

SCALE : NTF

APRVD BY : G.Y.


UNIT : mm [INCH]



RECOMMENDED OPERATING CONDITION Ta=-20~70℃ , VSS=0V

PARAMETER		MIN	TYP	MAX	UNITS	TEST COND
PROPAGATION DELAY TIME	TPLZ	-	-	300	ns	DIN→DOUT
						CL=15pF, RL=10KΩ
FALLING TIME	TTHZ	-	-	20	us	CL=300pF OUTR/OUTG/OUTB
INPUT CAPACITOR	Tci	-	-	15	pf	


TIMING WAVE FORM




HIGH SPEED MODE

ITEM	DESCRIPTION	TYP.	ALLOWANCE
T0H	0 CODE, HIGH-LEVEL TIME	300ns	±80ns
T0L	0 CODE, LOW-LEVEL TIME	900ns	±80ns
T1H	1 CODE, HIGH-LEVEL TIME	900ns	±80ns
T1L	1 CODE, LOW-LEVEL TIME	300ns	±80ns
RES	RESET TIME	>50us	-

DATA COMMUNICATION



SINGLE DATA IN 24BIT FOR RGB



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ^{+DECIMAL PRECISION}_{-0.00} MAX.= ^{+0.00}_{-DECIMAL PRECISION}

EXAMPLE OF USING STM32F030C8T6 TO DISPLAY RED, GREEN AND BLUE IN SEQUENCE

```

/*****/
uint32_t color;
void Display_One_Dot(uint32_t color);
void Send_Hi(void);
void Send_Lo(void);
void Init_GPIOs(void);
void main(void)
{
    Init_GPIOs();
    while (1)
    {
        color = 0xFF0000;
        Display_One_Dot(color);
        delay_ms(1000);
        color = 0x00FF00;
        Display_One_Dot(color);
        delay_ms(1000);
        color = 0x0000FF;
        Display_One_Dot(color);
        delay_ms(1000);
    }
}
/*****/
void Display_One_Dot(uint32_t color)
{
    uint8_t j=0;
    uint32_t x,y;
    y = color;
    for (j=0;j<24;j++)
    {
        x = (y & 0x800000);
        if (x>0)
            Send_Hi();
        else
            Send_Lo();
        y = y << 1;
    }
}

```

```

/*****/
void Send_Lo(void)
{
    GPIO_SetBits(GPIOB,GPIO_Pin_8);
    GPIO_ResetBits(GPIOB,GPIO_Pin_8);
    GPIO_ResetBits(GPIOB,GPIO_Pin_8);
    GPIO_ResetBits(GPIOB,GPIO_Pin_8);
}
/*****/
void Send_Hi(void)
{
    GPIO_SetBits(GPIOB,GPIO_Pin_8);
    GPIO_SetBits(GPIOB,GPIO_Pin_8);
    GPIO_SetBits(GPIOB,GPIO_Pin_8);
    GPIO_ResetBits(GPIOB,GPIO_Pin_8);
}
/*****/
void Init_GPIOs(void)
{
    GPIO_InitTypeDef GPIO_InitStructure;
    RCC_AHBPeriphClockCmd(RCC_AHBPeriph_GPIOB,ENABLE);
    GPIO_InitStructure.GPIO_Pin = GPIO_Pin_8 ;
    GPIO_InitStructure.GPIO_Mode = GPIO_Mode_OUT;
    GPIO_InitStructure.GPIO_OType = GPIO_OType_PP;
    GPIO_InitStructure.GPIO_PuPd = GPIO_PuPd_UP;
    GPIO_InitStructure.GPIO_Speed = GPIO_Speed_50MHz;
    GPIO_Init(GPIOB, &GPIO_InitStructure);
}

```