




UNCONTROLLED DOCUMENT



PART NUMBER		REV.
SSA-LXB10G7H3W		B
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10BRDR. & REDRAWN.	5.12.99
B	E.C.N. #11148	5.23.07

ELECTRO-OPTICAL CHARACTERISTICS		$T_A=25^{\circ}\text{C}$	$I_f=20\text{mA}$	
PARAMETER	GREEN	RED	UNITS	TEST COND
PEAK WAVELENGTH	565	700	nm	
FORWARD VOLTAGE (TYP.)	2.2	2.0	nm	
FORWARD VOLTAGE (MAX.)	2.6	2.5	V_f	
REVERSE VOLTAGE	5.0	5.0	V_r	$I_r=100\mu\text{A}$
AXIAL INTENSITY	6	3	mcd	$I_f=20\text{mA}$
VIEWING ANGLE	160	160	2x theta	
LED POSITION:	1~7	8~10		
EPOXY LENS FINISH:	MILKY WHITE DIFFUSED			
FACE COLOR:	BLACK			

LIMITS OF SAFE OPERATION AT 25°C PER CHIP			
PARAMETER	COLORS	MAX	UNITS
PEAK FORWARD CURRENT*		150	mA
STEADY CURRENT	(C/R)	25/30	mA
POWER DISSIPATION		105	mW
DERATE FROM 25°C		-1.6	mW/°C
OPERATING, STORAGE TEMP.		- 40 TO + 85	°C
SOLDERING TEMP.		+ 260	°C
2.0mm FROM BODY			3 SEC. MAX

* $t < 10 \mu s$

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.06 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=^{+DECIMAL PRECISION}_{-0.00} MAX.=^{+0.00}_{-DECIMAL PRECISION}

REV. B	PART NUMBER SSA-LXB10G7H3W	CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.		290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw		
10 SEGMENT BAR GRAPH, GREEN/RED COMBINATION, BLACK FACE WITH MILKY WHITE DIFFUSED EPOXY.			DRAWN BY: JN	CHECKED BY:	APPROVED BY:	DATE: 9.2.94 PAGE: 1 OF 1 SCALE: N/A