






PART NUMBER		SSA-LXB16I8Y8W	REV	D
REV	E.C.N. NUMBER AND REVISION COMMENTS			DATE
A	E.C.N. #11013.			07.11.03
B	E.C.N. #11032.			09.04.03
C	E.C.N. #11034.			09.18.03
D	ECN-Lumex201800001			01.04.18



POLARITY



ELECTRO-OPTICAL CHARACTERISTIC TA=25°C PER DICE

PARAMETER		MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH	R	-	635	-	nm	If=20mA
	Y	-	585	-		
FORWARD VOLTAGE	R	-	2.0	2.5	Vf	If=20mA
	Y	-	2.0	2.5		
REVERSE CURRENT		-	-	100	uA	VR=5V
LUMINOUS INTENSITY	R	-	8	-	mcd	If=10mA
	Y	-	8	-		
EMITTED COLOR		RED / YELLOW				
EPOXY LENS FINISH		MILKY WHITE DIFFUSED				
FACE COLOR		BLACK				

ABSOLUTE MAXIMUM RATINGS TA=25°C PER SEGMENT

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	100	mA
FORWARD CURRENT	25	mA
REVERSE VOLTAGE	5	V
POWER DISSIPATION	65	mW
STORAGE TEMPERATURE	-35 TO +85	°C
OPERATING TEMPERATURE	-35 TO +85	°C
SOLDERING TEMPERATURE**	3 SEC. MAX @ 260	°C

* t<10us
** AT 2mm DISTANCE FROM THE CASE OF REFLECTOR EDGE.

NOTE:
1. RoHS COMPLIANT.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ^{+DECIMAL PRECISION}/_{-0.00} MAX.= ^{+0.00}/_{-DECIMAL PRECISION}



425 N. GARY AVE.
CAROL STREAM, IL 60188
PHONE : 800-278-5666
FAX : 630-315-2150
WEB : WWW.LUMEX.COM

26.09(L)*8.40(W)*7.9(H)mm, 16 SEGMENT, CURVED LED ARRAY, 8-635nm RED CHIPS, 8-585nm YELLOW CHIPS, WHITE SEGMENTS, BLACK FACE, COMMON CATHODE.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE : 2018.01.04
PAGE : 1 OF 1
SCALE : NTF
UNIT : mm [INCH]

DRAWN BY : C.C.
CHKD BY : E.C.
APRVD BY : G.Y.
Ⓢ