


ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$ $I_f=20\text{mA}$

PARAMETER	GREEN	YELLOW	AMBER	RED	UNITS	TEST COND
PEAK WAVELENGTH	565	585	610	635	nm	
FORWARD VOLTAGE (TYP.)	2.0	2.0	2.1	2.2	V _f	
FORWARD VOLTAGE (MAX.)	2.5	2.5	2.5	2.6	V _f	
REVERSE VOLTAGE	5.0	5.0	5.0	5.0	V _r	$I_r=100\mu\text{A}$
AXIAL INTENSITY	15	10	10	10	mcd	$I_f=20\text{mA}$
VIEWING ANGLE	110	110	110	110	2x theta	
LED POSITION:	1,2	3	4	5		
EPOXY LENS FINISH:	DIFFUSED SAME AS EMITTED COLOR					

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	COLORS	MAX	UNITS
PEAK FORWARD CURRENT*		150	mA
STEADY CURRENT	(G/Y/A/R)	25/30/30/30	mA
POWER DISSIPATION		105	mW
DERATE FROM 25°C		-1.2	mW/ $^\circ\text{C}$
OPERATING, STORAGE TEMP.		-40 TO +85	$^\circ\text{C}$
SOLDERING TEMP.		+260	$^\circ\text{C}$
2.0mm FROM BODY			3 SEC. MAX

* $t < 10\mu\text{s}$

NOTES:

1. SSL-LX2583GD, LED. (2 PCS.)
2. SSL-LX2583YD, LED. (1 PCS.)
3. SSL-LX2583AD, LED. (1 PC.)
4. SSL-LX2583ID, LED. (1 PC.)
5. SSH-LXH525, HOLDER.
6. BACKFILL BOTTOM OF HOLDER WITH U.V. GLUE TO SECURE LEDS.

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV.

PART NUMBER

SSA-LXB525G2YAIDRP

1.8mm x 5.3mm 5 UNIT LED ARRAY,
 POS.1&2: GREEN, POS.3: YELLOW, POS.4: AMBER,
 POS.5: RED, COLOR DIFFUSED LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
 PALATINE, IL 60067-6976
 PHONE: +1.847.359.2790
 US WEB: www.lumex.com
 TW WEB: www.lumex.com.tw

DRAWN BY:

JN

CHECKED BY:

APPROVED BY:

DATE: 6.01.07

PAGE: 1 OF 1

SCALE: N/A