


UNCONTROLLED DOCUMENT



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.038), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=^{+DECIMAL PRECISION}_{-0.00}, MAX.=^{+0.00}_{-DECIMAL PRECISION}

SC:1

PART NUMBER

SSA-LXH1025-Q17750

REV.

PRELIMINARY IN P/N DIR

CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$ $V_f=5\text{V}$

PARAMETER	BLUE	YELLOW	AMBER	RED	UNITS	TEST COND
PEAK WAVELENGTH	430	585	605	635	nm	
FORWARD VOLTAGE (TYP.)	5.0	5.0	5.0	5.0	V_f	
FORWARD VOLTAGE (MAX.)	7.0	7.0	7.0	7.0	V_f	
REVERSE VOLTAGE	5.0	5.0	5.0	5.0	V_r	$I_r=100\mu\text{A}$
AXIAL INTENSITY	15	15	15	15	md	$V_f=5\text{V}$
VIEWING ANGLE	60	60	60	60	2x theta	
LED POSITION:	1,6	2,7	3,4,8,9	5,10		
EPOXY LENS FINISH:	DIFFUSED SAME AS EMITTED COLOR					

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	COLORS	MAX	UNITS
FORWARD VOLTAGE		7.0	V
STEADY CURRENT		12	mA
POWER DISSIPATION		310	mW
DERATE FROM 25°C		-1.2	mW/ $^\circ\text{C}$
OPERATING, STORAGE TEMP.		-40 TO +85	$^\circ\text{C}$
SOLDERING TEMP.		+260	$^\circ\text{C}$
2.0mm FROM BODY			3 SEC. MAX

NOTES:

- SSH-LXH1025 HOLDER. MATERIAL.: BLACK NYLON, UL V94-0.
- SSL-LX25583SBD-5V LED (2 PCS). UNCUT LEADS.
- SSL-LX25583YD-5V LED (2 PCS). UNCUT LEADS.
- SSL-LX25583AD-5V LED (4 PCS). UNCUT LEADS.
- SSL-LX25583ID-5V LED (2 PCS). UNCUT LEADS.
- SORT LEDS FOR MATCHED INTENSITY PER.

UNCONTROLLED DOCUMENT

REV.

PART NUMBER

SSA-LXH1025-Q17750

10 UNIT LED ARRAY, 2.5mm x 5mm RECTANGULAR LEDS,
BLUE, YELLOW, AMBER, AMBER, RED, BLUE, YELLOW, AMBER,
AMBER, RED, DIFFUSED PER COLOR, 5V OPERATION.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

GT

CHECKED BY:

APPROVED BY:

DATE: 1.21.03

PAGE: 1 OF 1

SCALE: N/A