

UNCONTROLLED DOCUMENT


SC:0.50

PART NUMBER

REV.

SSA-LXH509UWC-110

PRELIMINARY IN P/N DIR



NOTES:

1. MOLEX CONNECTOR 50-57-9403.
2. SSH-LXH509, WHITE POLYCARBONATE HOLDER, 94V-0.
3. SSL-LX5093XUWC, WHITE LED. (3 PCS. NOT PICTURED)
4. RED ANODE WIRE, 24 AWG.
5. BLACK CATHODE WIRE, 24 AWG.
6. CLEAR PLASTIC COVER.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION

REV.

PART NUMBER

SSA-LXH509UWC-110

3 UNIT, WHITE LED ARRAY.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

BC

CHECKED BY:

APPROVED BY:

DATE: 12.17.03

PAGE: 1 OF 1

SCALE: N/A